


KRP 16/13,5

Reduction adaptor, polyamide, RAL 7035, Pg16 / Pg13,5



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.



Material	Polyamide, fibre reinforced
Temp. range min	-40 °C
Temp. range max	100 °C
Glow wire test	650 °C
Thread type outer	PG
Ø outer thread	16
Length screw-in thread L	10 mm
Thread type inner	PG
Ø inner thread	13,5
Length internal thread	15,5 mm
Total length TL	28 mm
Key width SW	27 mm
Collar diameter (E)	30 mm
Form	A
Product Color	RAL 7035
Order no. RAL 7035	10063612
Type	KRP 16/13,5
Packing unit	100
ETIM-Classification	EC000938

Recommended accessories

MUG 16	10060674
ADR 16	10061423

Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com

08.02.2021

Your Contact:
WISKA Hoppmann GmbH
Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany
 +49-4191-508-0 ·  +49-4191-508-209
contact@wiska.de · www.wiska.com



Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com