

TOP PRODUCT

RP 50-S/RP 50-S INOX

Durable and precise: the weatherproof precision testing pump with TWIN VALVE-System for reliable measurement results



Double valve system: enables self-testing of the pump, as well as a precise fine adjustment of the pressure



Extra fine scaling Pressure gauge for the testing of systems up to 16 bar with a 0.2 scaling



Testing hose with steel mesh ensures reliable measurements



Technical data

Testing and pressure range	0–60 bar
Hub suction capacity	approx. 45 ml/stroke
Tank capacity	12 l
Connection	R 1/2"

Pressure gauge units	bar, psi, Mpa
Suitable for	oil, water and glycol
Product dimension	495 × 165 × 255 mm
Product weight	8.0 kg



No. 60200



No. 60203

P 50-S/RP 50-S INOX

Model			No.
RP 50-S testing pump	8.0	1	60200
RP 50-S INOX (stainless steel) testing pump	8.0	1	60203



1) Complete terms and conditions at rothenberger.com/roservice
RO SERVICE+ only valid in participating countries

Further test pumps

Model			No.
Testing pump TP 25	4.6	1	60250
Testing pump RP 30	4.5	1	61130
Testing pump RP PRO III self-priming with power cable, high-pressure hose	16		61185 (230 V) V12110016 (110 V)



No. 60250



No. 61130



No. 61185



No. 61316

Accessories

Description			No.
Maintenance package	100	1	60201
Double nipple 1/2" to 3/4"	100	1	60999
High pressure hose with 1/4" connection	490	1	R6112500
Extra 16 bar pressure gauge	100	1	61316

RP 50-S

RP 50-S INOX



More information at
rothenberger.com