

Accessories

» Solis Data Logging Box

Solis Monitoring System



Data Logging Box: GPRS

- Quick installation and easy operation
- GPRS communication supporting remote monitoring
- Multi-functional protections keeping your system from faults
- Keeping users informed of status and data via mobile device

Datasheet

| | |
|------------|-------------|
| Model Name | DLB-G(GPRS) |
|------------|-------------|

Communication

| | |
|-------------------------------|-------------------------------------|
| Number of connected inverters | 10 |
| Communaication interface | RS485 |
| Max. communication range | <1 km |
| Serial communication rate | 9600bps (adjustable:1200-57600 bps) |
| WiFi transmitting power | Class 4 (2W) / Class 1 (1W) |
| Data collection intervals | 5 minutes (adjustable:1-20 minutes) |
| Status indicator | LED × 4 |

Electrical

| | |
|-----------------------------|-------|
| Operating voltage | DC 5V |
| Operating power consumption | <8 W |

Environment

| | |
|-----------------------|-----------------------------------------|
| Operating temperature | -10 ~ +65°C |
| Operating humidity | 10%-90%, relative humidity, no condensa |
| Storage temperature | -40 ~ +65°C |
| Storage humidity | <40% |
| Protection degree | IP21 |

Mechanical

| | |
|--------------------|--------------|
| Dimensions (L*W*H) | 110*86*26 mm |
| Weight | 102 g |

Standard

| | |
|---------------|---------------|
| Certification | FCC, CE, RoHS |
|---------------|---------------|