

## 192A.VE - 1,000 VOLT INSULATED HIGH-PERFORMANCE DIAGONAL CUTTERS




### Standards :

NF ISO 5749, ISO 5749, DIN ISO 5749, ASME B107.500, NF EN 60900, EN 60900, DIN EN 60900

### Description :

- For your safety, all pliers are tested individually at 10,000 volts for 10 seconds, at the end of the manufacturing cycle.
- New head design to increase durability and cutting capacity
- Cutting edges designed to cleanly cut all types of wire: soft wires and modern materials to a maximum piano wire specification of: - 192A.16VE : 2.0mm 210 kg/mm<sup>2</sup> - 192A.18VE : 2.2mm 205 kg/mm<sup>2</sup>
- High mechanical advantage due to off-set rivet and cutting edge geometry reducing effort.
- High durability carbon alloy steel, with induction hardened cutting edges.
- Bi-Material ergonomic grips resistant to chemical agents.
- Return spring.
- Tether ready (Tether point adds 10mm to nominal length).
- Varnish finish to help prevent rusting.

### References :

	B [MM]	C [MM]	D MAXI [MM]	E [MM]	L [MM]	CU - Ø MAX [MM <sup>2</sup> ]	[G]
192A.16VE	24,0	18,0	2,0	10,0	160	0,7 - 4,0	200
192A.18VE	26,0	20,0	2,2	11,0	180	0,7 - 4,5	260