

Mini box type 3

Dual-wall heat shrink tubing / flexible / flame retardant / 3:1 / adhesive lined / H-5(3X)-F

Features:

- Crosslinked co-extruded adhesive lined Polyolefin
- Shrink ratio: 3:1
- Flame retardant
- Excellent sealing and insulation properties
- UV resistant
- Halogen free

Approvals:

- UL224 125 °C VW-1 600 V file E204071
- Meets: RoHS
- Meets: SAE-AMS-DTL-23053/4

Application:

- Operating temperature: -55 °C to +125 °C
- Minimum shrink temperature: +70 °C
- Minimum full recovery temperature: +110 °C
- Longitudinal change: 0 ± 10% max.

Order information:

- Color: black



Type / Size	As supplied: inside diameter in mm (min.)	After recovery: inside diameter in mm (max.)	After recovery: wall thickness in mm (min.)	Box / Meter
H-5(3X)-F 3:1 3,0/1,0	3,0	1,0	1,00	5,0
H-5(3X)-F 3:1 4,8/1,5	4,8	1,5	1,00	4,0
H-5(3X)-F 3:1 6,0/2,0	6,0	2,0	1,00	3,5
H-5(3X)-F 3:1 9,0/3,0	9,0	3,0	1,40	3,0
H-5(3X)-F 3:1 12,0/4,0	12,0	4,0	1,60	2,5
H-5(3X)-F 3:1 19,0/6,0	19,0	6,0	2,15	2,0
H-5(3X)-F 3:1 24,0/8,0	24,0	8,0	2,40	1,5