

Mini box type 5

Thin-wall heat shrink tubing / yellow/green striped / flexible / flame retardant / 2:1/3:1 / mil spec 135 degrees / H-2F(Y/G)

Features:

- Crosslinked Polyolefin
- Shrink ratio: 2:1 and 3:1
- Flame retardant
- High flexibility

Approvals:

- UL224 125 °C VW-1 600 V file E204071
- CSA file no.: 1934614
- Meets: RoHS
- Meets: SAE-AMS-DTL-23053/5 class 1

Application:

- Operating temperature: -55 °C to +135 °C
- Minimum shrink temperature: +70 °C
- Minimum full recovery temperature: +100 °C
- Longitudinal change: 0 ± 10% max.

Order information:

- Color: yellow / green



Shrink ratio 2:1

Type / Size	As supplied: inside diameter in mm (min.)	After recovery: inside diameter in mm (max.)	After recovery: wall thickness in mm (min.)	Box / Meter
H-2F(Y/G) 2.4/1.2	2.4	1.2	0.44	10
H-2F(Y/G) 3.2/1.6	3.2	1.6	0.44	10
H-2F(Y/G) 4.8/2.4	4.8	2.4	0.56	10
H-2F(Y/G) 6.4/3.2	6.4	3.2	0.56	5
H-2F(Y/G) 9.5/4.8	9.5	4.8	0.56	5
H-2F(Y/G) 12.7/6.4	12.7	6.4	0.65	5
H-2F(Y/G) 19.0/9.5	19.0	9.5	0.80	5

Shrink ratio 3:1

Type / Size	As supplied: inside diameter in mm (min.)	After recovery: inside diameter in mm (max.)	After recovery: wall thickness in mm (min.)	Box / Meter
H-2F(Y/G) 3.0/1.0	3.0	1.0	0.55	10
H-2F(Y/G) 4.5/1.5	4.5	1.5	0.60	10
H-2F(Y/G) 6.0/2.0	6.0	2.0	0.65	10
H-2F(Y/G) 9.0/3.0	9.0	3.0	0.75	5
H-2F(Y/G) 12.0/4.0	12.0	4.0	0.75	5
H-2F(Y/G) 18.0/6.0	18.0	6.0	0.85	5
H-2F(Y/G) 24.0/8.0	24.0	8.0	1.00	5