

## Maadoitusliitin

**EB..., EB .../ES**

**209 mm, 1/8-1 1/2in, D 8-50mm**

### KÄYTTÖTARKOITUS

Sinkittyjen teräsputkien tai kupariputkien maadoitus

### STANDARDIT

IEC 60364-4-41:2007, Pienjännitteiset sähköasennukset -...-  
Suojaa sähköiskuilta

### LIITTIMEN KOKO

2.5 ... 16 mm<sup>2</sup> kiinteää kuparilankaa; EB0, EBS0: 2,5 10 mm<sup>2</sup>

### MATERIAALIT

asennusnauha: ruostumaton teräs 1.4301  
liitinkokoonpano EB.. : teräs, sinkitty ja passivoitu  
liitinkokoonpano EB../ES: ruostumaton teräs 1.4301

### TURVALLISUUS

pyöristetyt reunat

### YMPÄRISTÖ

kaikki materiaalit ja valmistusprosessit ovat RoHS-säännösten mukaisia

### LISÄVARUSTEET

keltavihreä, kiinni napsautettava "EI SAA POISTAA"-  
varoitustarra

## Strip earthing clips

**EB..., EB .../ES**

**209 mm, 1/8-1 1/2in, D 8-50mm**

### APPLICATION

Earthing of galvanized steel tubes or copper tubes

### STANDARDS

IEC 60364-4-41:2007, Low voltage electrical installations -...-  
Protection against electric shock

### TERMINAL SIZE

2.5 ... 16 sqmm solid copper wire ; EB0 , EBS0 : 2,5 10 sqmm

### MATERIALS

mounting strip: stainless steel 1.4301  
terminal assembly EB.. : steel, zinc plated and passivated  
terminal assembly EB../ES: stainless steel 1.4301

### SAFETY

edges rounded

### ENVIRONMENT

all materials and manufacturing processes comply to RoHS regulations

### ACCESSORIES

yellow-green snap on warning sticker "DO NOT REMOVE"



Sähkönumero / Electrical code	SAP	Tuote / Product	EAN	Valmistajan tuotekoodi / Manufacturers part number	Tyyppi / Type	Vanteen pituus / Strip length	Putken kiinnitysalue, läpimitta / Tube size, dia
1916502	CQV494	MAADOITUSLIITIN ONNLINE 136 mm, 1/8-3/8in, D 8-22mm	4025221406307	5220116	EB 0	136 mm	1/8-3/8" / ø 8-22 mm
1916503	CQV495	MAADOITUSLIITIN ONNLINE 209 mm, 1/8-1 1/2in, D 8-50mm	4025221406314	5220117	EB 0-1	209 mm	1/8-1 1/2" / ø 8-50 mm
1916504	CQV496	MAADOITUSLIITIN ONNLINE 428 mm, 1/8-4in, D 8-114mm	4025221406321	5220118	EB 2	428 mm	1/8-4" / ø 8-114 mm
1916505	CQV497	MAADOITUSLIITIN ONNLINE 605 mm, 1/8-6in, D 8-165mm	4025221406338	5220119	EB 3	605 mm	1/8-6" / ø 8-165 mm