

6814U

Nimi: BasicLINE perus

Vahti-Jussi® BasicLINE perus, valkoinen

BasicLINE


Tyyppi: 6814U

EAN: 4011395148044

Snro: 2619332

Kuvaus: Yleiskäyttöinen läsnäolotunnistin sisätiloihin. Valvonta-alue 360°Ø 7m, kun laite on asennettu 2,5m korkeuteen. Valaistustason säätö 10 - 2000lux, katkaisuviive 5s - 30min. ja asennuskorkeus 2 - 4 metriä, IP40. Sivuohjaimena voidaan käyttää sulkeutuvia painonappeja. Uppoasennus alakattoon jousilukituksella tai koje/jakorasiaan, jolloin jouset on irroitettava.

Pakkaus: 1/24

Yksikkö: KPL

Tekniset tiedot
Mitat

Mitat 111x111x59 mm

Luokat

Kotelointiluokka IP40

Elektroniiikka

Valvonta-alue 360°

Lämpöolosuhteet

Käyttölämpötila 0 ... 45 °C

ETIM

ETIM 7 EC000133 (EC000133)

ETIM 8 EC000133 (EC000133)

ETIM 8

With DALI interface no

Constant light control no

HVAC-control no


Forced switch off no

Animal zone no

Creep-under protection yes

Networkable no

Optimum mounting height 2.5 m



6814U

Staircase monitoring	yes
Bridging switch	no
Diameter detection range on floor	7 m
Suitable for wireless transmission	no
Remote operation	no
With remote control	no
Response value sensitivity adjustable	no
Response value luminosity adjustable	yes
With signal unit	no
Teach-function for response value luminosity	no
Dim function with dimmer basic element	no
Mounting method	Flush mounted (plaster)
Material	Plastic
Material quality	Thermoplastic
Halogen free	yes
Surface protection	Untreated
Surface finishing	Matt
Colour	White
RAL-number (similar)	9010
Transparent	no
Degree of protection (IP)	IP40
Frequency	50 ... 60 Hz
Nominal voltage	230 V
Min. switch-on time	5 s
Max. duty cycle	30 min
Detection angle horizontal	30 ... 360 °
Pivoting range sensor, horizontal	
Pivoting range sensor, vertical	
Response value luminosity	10 ... 2000 lx
Max. switching power	2000 W
Suitable for C-load	no
Temperature	-20 ... 45 °C
Max. starting current	80 A
Substation input	yes
With alarm function	no