

Product Information

Name:

Coaxial outlets

Technical Data: 75 ohm, 7 dB

Colour: White/Black

Main material: PC (Halogen free)

IP-Class: IP20

Working temperature: -25°C to +60°C

Installation temperature: -5°C to +25°C

Fire hazard test: 650°C/850°C (IEC60695-2-11)

The product is in conformity with the provisions of the Following European directive(s): RoHS, WEEE

Technical info:

Flush mounted.

Special house (U240) for coaxial outlets - can be used when flush mounting cable installation enters as surface mounting, covering the flush box .

There has single screw (Pozidriv) in the cover plate.

Fit into wall boxes, screw distance c-c 60 mm.

With end terminator (75 ohm).

Thermoplastic center plate 55*55 mm, which fits into "U" series combination plate.



Electrical parameters:

	Parameter	Band Width	Specification
Insertion Loss	IN-TV	47-68 MHz	(11±2)dB
		125-860 MHz	(11±2)dB
	IN-RADIO	87.5-108 MHz	(11±2)dB
	IN-SAT	950-2300 MHz	(10±2)dB
	IN-OUT	47-1000 MHz	(2±1)dB
1000-2300 Mhz		(3±1)dB	

E-No.	Type	Description/Remark
	U213	TV/Radio

Drawing

