



VERSION	TRANSPORT TOT (kg)	CG			LLR		LL1 / LR1		LL2 / LR2	
		x	y	z	min.	min.	Y	Z	Y	Z
0102	940	635	1215	795	3500	1240	163	63	1640	63
0112	950	635	1210	805	3500	1240	163	63	1640	63
0122	1020	650	1150	795	3500	1240	163	63	1640	63
0142	1090	630	1095	785	3500	1240	163	63	1640	63

01	Updated description		12/01/2021	M. Delle Donne
REV. N°	DESCRIPTION		DATE	DRAWN
DESCRIPTION: NX2, NR2 (-Y, -Z) 0102..0142 G02, G06 WITH HYDRONIC KIT TNK A=2825			MITSUBISHI ELECTRIC HYDRONICS & IT COOLING SYSTEMS S.p.A.	
			SUBSTITUTES N° -	
DRAWN: M. Delle Donne		DATE: 16/07/2020	AUDITED: A. Sartore	SHEET 1 OF 2
Scale 1:20	Size A3	CONFIDENTIAL DOCUMENT PROPERTY OF MEHITS SPA IT CANNOT BE REPRODUCED NOR DELIVERED WITHOUT COMPANY WRITTEN CONSENT		DRAWING N° D1U1185003
				REV. N° 01

DIMENSIONS																				
VERSION									Evin Fix Flow Pumps HH			Evin Fix Flow Pumps LH			Evin Variable Flow Pumps			EVout		
	A	B	BS	H	R1	R2	R3	R4	X	Y	Z	X	Y	Z	X	Y	Z	X	Y	Z
0102	2825	1195	70	1980	1000	1000	1000	1000	1234	2266	261	1254	2266	261	1206	2266	261	1189	1037	217
0112	2825	1195	70	1980	1000	1000	1000	1000	1234	2266	261	1254	2266	261	1206	2266	261	1189	1037	217
0122	2825	1195	70	1980	1000	1000	1000	1000	1234	2266	261	1254	2266	261	1206	2266	261	1189	1054	217
0142	2825	1195	70	1980	1000	1000	1000	1000	1234	2266	261	1254	2266	261	1206	2266	261	1189	1078	217

DIMENSIONS										
VERSION	DSin			DSout			PS			
	X	Y	Z	X	Y	Z	X	Y	Z	DIM
0102	1109	903	1084	1109	903	850	1150	0	250	56x160
0112	1109	903	1084	1109	903	850	1150	0	250	56x160
0122	1109	857	1084	1109	857	850	1150	0	250	56x160
0142	1109	857	1084	1109	857	850	1150	0	250	56x160

HYDRONIC CONNECTIONS								
VERSION	EVin		EVout		DSin		DSout	
	TYPE	∅	TYPE	∅	TYPE	∅	TYPE	∅
0102	[B1]	76,1 (2"1/2)	[B1]	76,1 (2"1/2)	[B1]	42,1 (1"1/4)	[B1]	42,1 (1"1/4)
0112	[B1]	76,1 (2"1/2)	[B1]	76,1 (2"1/2)	[B1]	42,1 (1"1/4)	[B1]	42,1 (1"1/4)
0122	[B1]	76,1 (2"1/2)	[B1]	76,1 (2"1/2)	[B1]	42,1 (1"1/4)	[B1]	42,1 (1"1/4)
0142	[B1]	76,1 (2"1/2)	[B1]	76,1 (2"1/2)	[B1]	42,1 (1"1/4)	[B1]	42,1 (1"1/4)

[B1] = Male threaded pipe (EN 10226 - R: external taper thread)

DAMPER POSITIONING								
VERSION	AVL1		AVR1		AVL2		AVR2	
	X	Y	X	Y	X	Y	X	Y
0102	53.5	72.5	1141.5	72.5	53.5	2290	1141.5	2290
0112	53.5	72.5	1141.5	72.5	53.5	2290	1141.5	2290
0122	53.5	72.5	1141.5	72.5	53.5	2290	1141.5	2290
0142	53.5	72.5	1141.5	72.5	53.5	2290	1141.5	2290

WEIGHT DISTRIBUTION (kg) - RUBBER DAMPERS					
VERSION	TOT	AVL1	AVR1	AVL2	AVR2
0102	1100	250	239	311	300
		FZ-200-57	FZ-200-57	FZ-200-57	FZ-200-57
0112	1110	253	242	313	302
		FZ-200-57	FZ-200-57	FZ-200-57	FZ-200-57
0122	1180	277	280	310	313
		FZ-200-57	FZ-200-57	FZ-200-57	FZ-200-57
0142	1260	317	308	322	313
		FZ-200-57	FZ-200-57	FZ-200-57	FZ-200-57

FORKLIFT BRACKETS (OPTION)					
VERSION	MFL	FL1 / FR1		FL2 / FR2	
	min	Y	WxH	Y	WxH
0102	150	651	157x70	1407.5	157x70
0112	150	651	157x70	1407.5	157x70
0122	150	651	157x70	1407.5	157x70
0142	150	651	157x70	1407.5	157x70