

part number cable family

46400 O.R. FRX® PLUS

FORMATION: 4G2,50

4GAWG14

INSTALLATION TYPE: CABLE FOR DYNAMIC INSTALLATION ON DRAG CHAIN

CATEGORY: MULTI CORE

STANDARD/APPROVAL: CE/UL/CSA

SHIELDING: UNSHIELDED



GROUP // 4G2,50

CONDUCTOR

MATERIAL	Bare copper
CAPILLARY DIAMETER	- Extra-flexible (DIN VDE 0295, IEC 60228 or CEI 20-29)
CONDUCTORS NUMBER	4
RATED SECTION	2,50 mm ²

INSULATION

MATERIAL	Polyolefin
COLOUR	Black conductors with numbers from 1 to 3 + Green/Yellow.

TOTAL ASSEMBLY MAKE-UP

TOTAL TAPING

ON MAKE-UP	Around the total assembly.
MATERIAL	Non-woven tape

TOTAL SHEATH

COLOUR	Gray RAL 7001
DIAMETER (MM)	9,2±0,3



MARKING

METRIC MARKING

P/N ***** TE.CO. E244280 - Fxx - cRUus -
AWM STYLE 21179 90°C 1000V VW-1 - AWM
I/II A/B 90°C 1000V FT1 - nxXAWG - O.R.
FRX® nGY - IEC 60332-1-2 - year/week - CE
meter indication

ELECTRICAL FEATURES

WORKING VOLTAGE	1000 V
TEST VOLTAGE	4000 V
INSULATION RESISTANCE	>=1 Gohm/Km acc. to EN 50395 prt.8

DYNAMIC FEATURES

MINIMUM BENDING RADIUS STATIC INSTALLATION	4 times \varnothing cable
MINIMUM BENDING RADIUS DYNAMIC INSTALLATION	7.5 times \varnothing cable
WORKING TEMPERATURE STATIC INSTALLATION	-40°C / +90°C
WORKING TEMPERATURE DYNAMIC INSTALLATION	-5°C / +90°C
TRAVEL SPEED	Up to 180 m/min
ACCELERATION/DECELERATION	Up to 10 m/sec ²
CABLE LENGTH INSIDE CHAIN	Up to 20 m
CHAIN LENGTH NOTES	(horizontal only)
GUARANTEED CYCLES	Up to 5 Mio
NOTES	The given data are meant to be restricted to the type of reference installation. For fixed installation is meant to be without any mechanical stress. For application in dynamic installation with very low temperatures, contact our technical department.

APPROVALS AND STANDARDS

REFERENCE STANDARDS

1581, UL 758(UL); C22.2 n° 210(CSA);
Referring to DIN VDE 0207,0285,0819 and
0295.

UL CSA APPROVALS

RU E244280 AWM STYLE 21179 90°C 1000V
CSA E244280 AWM I/II A/B 90°C 1000V

FIRE BEHAVIOUR

VW-1(UL); FT1(CSA); IEC 60332-1-2(EU); DIN
VDE 0482-332-1-2; DIN EN 60 332-1-2; UL
CABLE FLAME

INDUSTRIAL OIL RESISTANCE

1581(UL); IEC 60811-404(EU); CEI EN 50363-
4-1(EU); VDE 0473-811-404

HALOGEN FREE

NO

UV RESISTANCE

ASTM ASTM-D-2565-16; EN 50289-4-17(EU);
ISO 4892-2

CUSTOMS CODE

CUSTOMS-TARIFF NUMBER

85444999

MADE IN

IT

REVISION

DATE

25112020

NUMBER

006