

Eaton C10G2

Catalog Number: C10G2

Eaton Bussmann series low voltage 10 x 38 mm cylindrical/ferrule fuse, rated at 500 Volts AC, 2 Amps, 120 kA Breaking capacity, class gG/gL, without indicator, compatible with a CHM Modular fuse holder



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage cylindrical fuse	C10G2
	EAN
	5027590493468
UPC	Product Length/Depth
051712754224	38 mm
Product Height	Product Width
10 mm	10 mm
Product Weight	Compliances
8.2 g	RoHS Compliant
	CE Marked
	GoST-R
Certifications	
IEC 60269	

Type

fuse

Application

for industrial applications
for general purpose use

Amperage Rating

2 A

Fuse size

10 x 38 mm

Current type

AC

Breaking capacity

120 kA

Frequency rating - max

62 Hz

Frequency rating - min

45 Hz

Rated voltage AC

500 V

Class

Class C gL/gG

Fuse type

C10G

Utilization category

gL/gG (cable protection/equipment protection)

Fuse indicator

Other

Watt losses

0.6 W

Connection

Ferrule end x ferrule end

Construction size

10 mm x 38 mm

Fuse shape

Cylindrical

Voltage type

AC

Suitable for

CHM Modular fuse holder

Material

Ceramic

Mounting method

Holder

Packaging type

Standard

Release characteristic

Other

Quantity

10

Voltage rating

500 V



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. Kaikki
oikeudet pidätetään.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)