


# 302EUJW-84

Nimi: **Pistorasia**  
 Pistorasia, Impressivo, 2-os, maad, jousiliittimin, haaroitusliittimet, IP44  
 IMPRESSIVO®

Tyyppi: 302EUJW-84  
 EAN: 6438199000046  
 Snro: 2516133

Kuvaus: Uppoasennettava roiskevesitiivis pistorasia. Pistorasiassa on liittimet kutakin kosketinta kohden ja niihin voi kytkeä max 4 johtoa (haaroitusmahdollisuus). Liittimet on hyväksytty ML ja MK johtimille. Ei potentiaalivapaita liittimiä. Pistorasian runko on kosketussuojainen ilman peitelevyä. IP44 hyväksytty vaaka suoraan ja läppäkannet ylös päin auki asennettuna. Toimitus sisältää myös peitelevyn.

Pakkaus: 1/10  
 Yksikkö: KPL



## Tekniset tiedot

### Luokat

Koteloitiluokka IP44

### Sähkösuureet

Nimellisvirta 16 A  
 Nimellisjännite 250 V

### ETIM

ETIM 7 EC000125 (EC000125)  
 ETIM 8 EC000125 (EC000125)

### ETIM 7

Model Protective contact (SCHUKO)  
 Protective contact yes  
 Protective earth pin round no  
 Number of active Pins (round)  
 Number of active Pins (flat)  
 With signal lamp no  
 With built-in USB power supply no  
 Number of units 2  
 Number of modules (module system) 1  
 Number of socket outlets switchable

# 302EUJW-84

Number of phases	1
Imprint/indication	Without imprint
Connection type	Plug clamp
With hinged lid	no
With child-protection	yes
Label space/information surface	no
Colour	White
RAL-number (akin)	9016
Transparent	no
Lockable	no
Eject-mechanism	no
Insulated mounting	no
With function lighting	no
With orientation lighting	no
Over voltage protection	no
Fault current protection	no
With miniature fuse	no
Special power supply	No special power supply
Mounting method	Flush mounted (plaster)
Type of fastening	Mounting with claw and screw
Material	Plastic
Material quality	Thermoplastic
Halogen free	yes
Surface protection	Untreated
Surface finishing	Glossy
Antibacterial treatment	no
With on/off switch	no
With loop through function	no
Rotated central insert	no
Nominal current	16 A
Nominal voltage	250 V
Frequency	50 Hz
Suitable for degree of protection (IP)	IP21
For heavy conditions (in accordance with VDE)	no
Width of device	85 mm
Height of device	100 mm
Depth of device	41 mm
Min. depth of built-in installation box	17 mm