

302EUJW-885

Nimi: **Pistorasia**

Pistorasia, Impressivo, 2-os, maad, jousiliittimin, haaroitusliittimet, IP44, matta musta

IMPRESSIVO®

Tyyppi: 302EUJW-885


EAN: 6438199008615

Snro: 2516135

Kuvaus: Uppoasennettava roiskevesitiivis pistorasia. Pistorasiassa on liittimet kutakin kosketinta kohden ja niihin voi kytkeä max 4 johtoa (haaroitusmahdollisuus). Liittimet on hyväksytty ML ja MK johtimille. Ei potentiaalivapaita liittimiä. Pistorasian runko on kosketussuojainen ilman peitelevyä. IP44 hyväksytty vaaka suoraan ja läppäkannet ylös päin auki asennettuna. Toimitus sisältää myös peitelevyn.

Pakkaus: 1/10

Yksikkö: KPL

**Luokat**

Kotelointiluokka IP44

Sähkösuureet

Nimellisvirta 16 A

Nimellisjännite 250 V

ETIM

ETIM 7 EC000125 (EC000125)

ETIM 8 EC000125 (EC000125)

ETIM 7

Model Protective contact (SCHUKO)

Protective contact yes

Protective earth pin round no

Number of active Pins (round)

Number of active Pins (flat)

With signal lamp no

With built-in USB power supply no

Number of units 2

Number of modules (module system) 1

Number of socket outlets switchable

Number of phases 1

Imprint/indication Without imprint

302EUJW-885

Connection type	Plug clamp
With hinged lid	no
With child-protection	yes
Label space/information surface	no
Colour	Black
RAL-number (akin)	9005
Transparent	no
Lockable	no
Eject-mechanism	no
Insulated mounting	no
With function lighting	no
With orientation lighting	no
Over voltage protection	no
Fault current protection	no
With miniature fuse	no
Special power supply	No special power supply
Mounting method	Flush mounted (plaster)
Type of fastening	Mounting with claw and screw
Material	Plastic
Material quality	Thermoplastic
Halogen free	yes
Surface protection	Lacquered
Surface finishing	Matt
Antibacterial treatment	no
With on/off switch	no
With loop through function	no
Rotated central insert	no
Nominal current	16 A
Nominal voltage	250 V
Frequency	50 Hz
Suitable for degree of protection (IP)	IP21
For heavy conditions (in accordance with VDE)	no
Width of device	85 mm
Height of device	100 mm
Depth of device	41 mm
Min. depth of built-in installation box	17 mm