

Indoor light

RS 14 L

EAN 4007841731113



Functional description

Glass can break, impact-resistant plastic can't. As the robust version of the classic light, this is why the RS 14 L is recommended for use as ceiling or wall lighting in corridors and stairwells in residential complexes. Same design, features and technology as the RS 10 L: classically understated with high-frequency sensor system in a class of its own.

Technical specifications

Dimensions (Ø x H)	280 x 110 mm
Mains power supply	230 – 240 V , 50 / 50 Hz
Sensor Technology	High frequency
Transmitter power	< 1 mW
Output	60 W
Switching output 1, resistive	800 W
With lamp	No
Lamp	All-purpose lamp
Base	E27
With motion detector	Yes
Detection	also through glass, wood and stud walls
Detection angle	360 °
Angle of aperture	160 °
Electronic scalability	Yes
Mechanical scalability	No
Photo-cell controller	Yes
Twilight setting	2 – 2000 lx
Time setting	5 s – 15 min
Impact resistance	IK00
IP rating	IP44
Protection class	II
Ambient temperature	-20 – 40 °C
Housing material	Plastic
Cover material	Plastic, opal
Manufacturer's Warranty	5 years

Indoor light

RS 14 L

EAN 4007841731113

Light distribution curve 1

Sensorenerfassungsbereich 1

