


Floodlight

XLED slim

EAN 4007841012069



Functional description

When visitors arrive, light comes into play with the economical outdoor floodlight XLED slim. This stylish lighting solution captivates with its elegant design and provides attractive illumination for building entrances and pathways. On building facades the XLED slim makes attractive lighting statements that not only look good but also ensure you get home safely. At the same time, the unobtrusive floodlight with its almost invisible sensor blends into the background with visual discretion.

Technical specifications

Dimensions (L x W x H)	241 x 66 x 201 mm
Mains power supply	230 – 240 V , 50 / 60 Hz
Sensor Technology	passive infrared
Output	10,5 W
Luminous flux	660 lm
Colour temperature	4000 K
Colour variation LED	SDCM3
Colour Rendering Index CRI	80-89
With lamp	Yes, STEINEL LED system
Lamp	LED cannot be replaced
LED life expectancy (max. °C)	50000 h
Drop in luminous flux in accordance with LM80	L70B10
LED cooling system	Active and Passive Thermo Control
With motion detector	Yes
Detection angle	160 °
Sneak-by guard	Yes
Reach, tangential	r = 8 m (89 m²)
Photo-cell controller	Yes
Time setting	2 s – 70 min
Impact resistance	IK00
IP rating	IP44
Protection class	I
Housing material	Aluminium
Cover material	Plastic, transparent
Manufacturer's Warranty	3 years
PU1, net weight	0,549 kg
Version	white