



**Weight:** 8kg

**Dimensions:** L 180mm W 130mm H 130mm

**Compliance:** Explosion protected to AS/NZS1299 IEC Ex

**Materials:** Manganese Bronze / Brass / PTFE

**IP Rating:** IP66/68

**Ordering Procedure**

- ❶ Select Complete Receptacle from Table 1
- ❷ Select Phase Thimble from Table 2(3 required)

**Table 1**

Part No.	Description	Colour
AG664B	660V Restrained Receptacle	Orange
AG614B	1100V Restrained Receptacle	Blue

**Table 2**

**Phase Thimble - c/w item 10**

Part No.	Cable CSA mm <sup>2</sup>	ID mm	Utilux Die No.
4570	2.5	3	38-44 Cu
4570-1	6	3.7	38-44 Cu
4570-2	10	4.7	38-57 Cu
4570-3	16	5.5	38-63 Cu

**Spare Parts**

Item	Part no.	Description
1	3856	Jacking Screw
2	F-309	Sealing Plug
3A	F-3492-664	660V Receptacle Body c/w items 1,3A&11
3B	F-3492-614	1100V Receptacle Body c/w items 1,3B&11
4	F-4566	Phase Contact Pin c/w O-ring AI019007
5	F-4569	Pilot Contact Pin c/w O-ring AI019007
6	AI019008	O-ring ID 47.35 sect. 1.78
7	See Table 2	Phase Thimble
8	F-4564	Interior c/w item 6, 9, 10 & 11
9	F-4650	Earth Thimble c/w screw AH151035 M3 x 10 csk. head
10	4571	Interior Retaining Plate
11	AH151034	Screw M5 x 12 csk. Head
12	AI019006	O-ring ID 82.14 sect. 3.53
13	AH009277	Washer 5/16"
14	AH009363	Spring Washer 5/16"
15	AH113091	Earth Screw M8 x 10 hex. Head
16	4401-1	Seal