

Tuotetiedot

Tuotekoodi	VB04-0022	Sähkönumero	5201287	EAN-koodi	6410052012878
Tuotenimi	Pienjännitejatkospakkaus Al 3x6-50 + Al/Cu 6-25 mm ²			ETIM-luokka	EC001169
Johtimet	Al 3x16-50 + Al/Cu 6-25 mm ²				








Tekniset tiedot

	-	
	-	
Nimellisjännite (IEC)	1000	V
	-	
	-	
	-	
	-	
	-	
	-	
	-	
	-	
	-	
	-	
	-	
	-	
Paino	575	g
	-	
Standardit	EN 61238-1:2003	
Väri / Materiaali	Alumiini, Modifioitu polyeteeni	
Kiinnitys / Kytkenä	Momenttiruuvi	


Kuvaus

Jatkokset on tarkoitettu 4-johtimisten <1 kV käyttöjännitteen kaapelien jatkamiseen. Pakkaukset sisältävät neljä jatkoliitintä, neljä liimallista johdinkutistusta, yhden liimallisen kaapelikutisteen, hiomapaperia ja kaapelinpuhdistusliinan. Liittimissä on valmiiksi liitosrasvalla käsitellyt kytkentätilat. Liittimet asennetaan momenttiruuveilla sekä kuusiokoloavaimella (6-25 liitin).

Mittakuva

							
VB04-0022 16-50 (+6-25) mm ²	1x D65/L550	3x D22/L142 + 1x D16/L110	1x VB04-0015	3x VB04-0016	1x TB01-0042	1x TB01-0043	1x OE04-0611

Pakkaus

Pakkausmuoto	Pussi	Kpl / Pakkaus	1	Paino [kg]	0,58
Pituus [mm]	650	Leveys [mm]	100	Korkeus [mm]	70

Ouneva Oy

Teollisuustie 21
FI-82730 Tuupovaara
Finland

Tel. +358 400 179 750
info@ouneva.fi

www.ounevagroup.fi
www.ounevaproducs.fi

Product data

Product code	VB04-0022	STK-code	5201287	EAN-code	6410052012878
Product name	Low Voltage Joint kit Al 3x16-50 + Al/Cu 6-25 mm ²			ETIM class	EC001169
Wires	Al 3x16-50 + Al/Cu 6-25 mm ²				

Technical data

	-
	-
Nominal voltage (IEC)	1000 V
	-
	-
	-
	-
	-
	-
	-
	-
	-
	-
	-
	-
	-
	-
	-
	-
	-
	-
	-
Weight	575 g
	-










Standards	EN 61238-1:2003
Color / Material	Aluminium, Modified polyethylene
Mounting / Connection	Shear bolt

Description

Kit can be used connecting 4-conductor <1 kV Voltage cables. Package includes four connectors, four inner heat shrink tubes for conductors, one outer heat shrink tube for cable, sandpaper and cleaning wipe. Connectors are pretreated with connection grease for the corrosion prevention. Installation is made with shear head screws and allen key (6-25 connector).

Drawing

							
VB04-0022 16-50 (+6-25) mm ²	1x D65/L550	3x D22/L142 + 1x D16/L110	1x VB04-0015	3x VB04-0016	1x TB01-0042	1x TB01-0043	1x OE04-0611

Package

Package	Bag	Pcs / Package	1	Weight [kg]	0,58
Length [mm]	650	Width [mm]	100	Height [mm]	70

Ouneva Oy

Teollisuustie 21
FI-82730 Tuupovaara
Finland

Tel. +358 400 179 750
info@ouneva.fi

www.ounevagroup.fi
www.ounevaproducts.fi