

MODEL		MPW 3
Type		2 pipes
Codes - Models with infrared remote control		MPW3B5X
Codes - Models without infrared remote control		MPW3B5B
Cooling capacity	Units	
Total cooling capacity 7/12°C (LS/MS/HS)(1)	kW	1,91/2,53/3,17
Sensible cooling capacity 7/12°C (LS/MS/HS)(1)	kW	1,53/1,89/2,56
Heating capacity		
Heating capacity 50° C (LS/MS/HS) (2)	kW	2,70/3,50/4,50
Electric heating element	kW	-
Air flow rate (LS/MS/HS)	m ³ /h	320/400/510
Circuit specifications and connections		
Water flow rate at maximum power in cooling	m ³ /h	0,54
Pressure drop at maximum power in cooling (3)	kPa	29
Pressure drop at maximum power in heating (3)	kPa	27
Hidraulic connection		1/2" F - GAZ
Condensate discharge		Outer diameter end 18 mm
Electrical specifications		
Power 50 Hz		230/1
Maximum power consumption	W	73
Running noise		
Sound power per EN12102 (LS/MS/HS)	dBA	46/52/58
Sound pressure level at 2 m (LS/MS/HS)	dBA	37/43/49
Operating range		
Operating range water temperature	°C	+4°C / +60°C

- 1) Indoor temperature in cooling: +27°C D.B./ + 19°C W.B.
- 2) Indoor temperature in heating: +20°C.
- 3) Pressure drop for water without glycol.