

MODEL		CWX 3 B
Type		2 pipe coils
Codes - Models with remote control		CWX 3B5X
Codes grille - Models with remote control		K70N129T
Features	Units	
Total cooling capacity (HS/MS/LS) ⁽¹⁾	kW	2,60/2,35/2,15
Sensible cooling capacity (HS/MS/LS) ⁽¹⁾	kW	2,31/2,09/1,91
Heating capacity (HS/MS/LS) ⁽²⁾	kW	3,49/3,11/2,83
Heating capacity with electric heating element	kW	-
Heating capacity additional coil (HS/MS/LS) ⁽³⁾	kW	-
Air flow rate (HS/MS/LS)	m ³ /h	520/460/400
Air flow rate (HS/MS/LS)	m ³ /s	0,11/0,128/0,144
Water flow rate in cooling mode (HS) ⁽¹⁾	l/h	447
Water flow rate - additional coil ⁽³⁾	l/h	-
Pressure drop in cooling mode (HS) ⁽¹⁾	kPa	22
Pressure drop in heating mode (HS) ⁽²⁾	kPa	18
Water pressure drop additional coil (HS) ⁽²⁾	kPa	-
Electricity supply	V/Ph/Hz	230/1/50
Max. power consumption (HS)	kW	0,060
Max. total current (HS)	A	0,25
Hydraulic connection		1/2" G female
Sound power level (HS/MS/LS)	dBA	46/43/40
Sound pressure level (HS/MS/LS) at 2 m	dBA	37/34/31
Net dimension (H./W./D.)	mm	296x575x575
Net dimension grille (H./W./D.)		41x730x730
Net weight grille	kg	21

The pressure levels of Technibel products conform to European standard EN 12102

Nominal conditions

⁽¹⁾ T. Air inlet: +27°C D.B./ + 19°C W.B.

T. Water inlet: +7°C

T. Water outlet: +12°C

⁽²⁾ T. Air inlet: +20°C

T. Water inlet: +50°C / same water flow as in condition (1) (2 pipes)

⁽³⁾ T. Air inlet: +20°C

T. Water inlet: +70°C (4 pipes)

T. Water outlet: +60°C (4 pipes)

