

PRODUCT NAME		CSKF1485R5/7	
Indoor unit		CAFP485R5I	
Outdoor unit		GRFP485R5I/GRFP480R7IAA/GRFP480R7IAB	
Features	Units	Cooling	Heating
Cooling/Heating capacity	kW	12,50 (2,7-14,0)	14,00 (2,7-16,00)
	BTU/h	42.500	48.000
	kcal/h	10.750	12.040
Energy label class	ABCDEFGF	-	-
E.E.R. / C.O.P.	(kW/kW)	2,81	3,32
Air flowrate Indoor (h.m.l.)	m <sup>3</sup> /h	1.920-1.680-1.320	
Dehumidification	l/h	6,3	
Fan speeds (Indoor / Outdoor)	n°	3 + Auto / variable	
Sound pressure Indoor (h.m.l.)	dB(A)	53-50-46	
Sound pressure Outdoor (h.)	dB(A)	52/51	53/54
Power supply	V/Ph/Hz	230/1/50 - 400/3/50	
Running consumption	kW	3,86/4,45	3,83/4,22
Annual energy cons.- cooling mode (500h) - Directive 2002/31/CE	kWh	-	-
Compressor type		DCInverter Twin Rotary	
Refrigerant type		R410A	
Liquid pipe diameter	mm(inch")	9,52(3/8")	
Gas pipe diameter	mm(inch")	15,88(5/8")	
Max. pipe lenght with gas standard charge	m	30	
Max. pipe lenght with gas additional charge	m	50	
Max. height between units (Outdoor on top)	m	30	
Max. height between units (Indoor on top)	m	15	
Net weight Indoor (with grille) / Outdoor	Kg	35 / 100 - 76	
Net dimension Indoor (with grille) (H./W./D.)	mm	338x1.150x860	
Net dimension Outdoor (H./W./D.)	mm	1.230x940x340/910x940x340	