

PRODUCT NAME		CSKFI365R5/7	
Indoor unit		CAFP365R5I	
Outdoor unit		GRFP365R5I/GRFP360R7IAA/GRFP360R7IAB	
Features	Units	Cooling	Heating
Cooling/Heating capacity	kW	10,00 (2,2-11,2)	11,20 (2,2-12,50)
	BTU/h	34.000	38.000
	kcal/h	8.600	9.630
Energy label class	ABCDEFGF	A	A
E.E.R. / C.O.P.	(kW/kW)	3,21	3,78
Air flowrate Indoor (h.m.l.)	m <sup>3</sup> /h	1.920-1.680-1.320	
Dehumidification	l/h	4,6	
Fan speeds (Indoor / Outdoor)	n°	3 + Auto / variable	
Sound pressure Indoor (h.m.l.)	dB(A)	53-50-46	
Sound pressure Outdoor (h.)	dB(A)	51	52
Power supply	V/Ph/Hz	230/1/50 - 400/3/50	
Running consumption	kW	3,12	2,96
Annual energy cons.- cooling mode (500h) - Directive 2002/31/CE	kWh	1.560	-
Compressor type		DC Inverter Twin Rotary	
Refrigerant type		R410A	
Liquid pipe diameter	mm(inch")	9,52(3/8")	
Gas pipe diameter	mm(inch")	15,88(5/8")	
Max. pipe lenght with gas standard charge	m	30	
Max. pipe lenght with gas additional charge	m	50	
Max. height between units (Outdoor on top)	m	30	
Max. height between units (Indoor on top)	m	15	
Net weight Indoor (with grille) / Outdoor	Kg	35/65	
Net dimension Indoor (with grille) (H./W./D.)	mm	338x1.150x860	
Net dimension Outdoor (H./W./D.)	mm	780x940x340	

The technical data here indicated are in compliance with the European standard EN14511 - Directive 2002/31/EC