

INDOOR UNIT FOR MULTI-PACKAGE DC INVERTER SYSTEMS		MAFP 125 R5I		MAFP 165 R5I		MAFP 185 R5I		MAFP 255 R5I	
Features		Cooling	Heating	Cooling	Heating	Cooling	Heating	Cooling	Heating
Cooling/Heating capacity nominal	kW	3,6	4,2	4,5	5	5,6	6,3	7,3	8,0
	BTU/h	12.280	14.320	15.350	17.050	19.100	21.480	24.900	27.280
	kcal/h	4.000	3.610	3.870	4.300	4.820	5.420	6.280	6.880
Air flowrate (h.-m.-l.)	m ³ /h	720-600-420		720-600-420		780-660-480		1.140-1.020-840	
Dehumidification	l/h	1,9	-	1,9	-	2,1	-	4	-
Fan speeds	n°	3 + Auto		3 + Auto		3 + Auto		3 + Auto	
Sound pressure (h.-m.-l.) 2 m	dB(A)	35-31-27		35-31-27		38-34-30		41-37-34	
Sound power (h.-m.-l.)	dB(A)	44-40-36		44-40-36		47-43-39		50-46-43	
Power supply	V/Ph/Hz	230/1/50		230/1/50		230/1/50		230/1/50	
Power input	kW	0,033	0,033	0,033	0,033	0,033	0,033	0,052	0,052
Running current	A	0,15	0,15	0,15	0,15	0,15	0,15	0,23	0,23
Liquid pipe diameter	mm(inch")	6,35(1/4")		6,35(1/4")		6,35(1/4")		9,52(3/8")	
Gas pipe diameter	mm(inch")	12,7 (1/2")		12,7 (1/2")		12,7 (1/2")		15,88(5/8")	
Internal diameter of condensate drain pipe	mm	18		18		18		18	
Net weight	Kg	12		12		12		21	
Net dimension Indoor (H./W./D.)	mm	285x995x203		285x995x203		285x995x203		330x1140x228	