

MODEL		CWX 8
Type		2 pipes
Codes - Models without remote control		CWX 8B5B
Codes grille - Models without remote control		K70N095 T
Features	Units	
Total cooling capacity (HS/MS/LS) ⁽¹⁾	kW	8,00/6,50/5,50
Sensible cooling capacity (HS/MS/LS) ⁽¹⁾	kW	6,40/5,40/4,10
Heating capacity (HS/MS/LS) ⁽²⁾	kW	9,42/8,52/6,28
Air flow rate (HS/MS/LS)	m ³ /h	1270/1090/830
Air flow rate (HS/MS/LS)	m ³ /s	0,353/0,303/0,231
Water flow rate in cooling mode (HS) ⁽¹⁾	l/h	1380
Pressure drop in cooling mode (HS) ⁽¹⁾	kPa	41
Pressure drop in heating mode (HS) ⁽²⁾	kPa	39
Electricity supply	V/Ph/Hz	230/1/50
Maximum power consumption (HS)	kW	0,120
Maximum total current (HS)	A	0,5
Hydraulic connection		3/4" G female
Sound power level (HS/MS/LS)	dB(A)	50/46/37
Sound pressure level (HS/MS/LS) at 2 m	dB(A)	41/37/28
Net dimension (H./W./D.)	mm	340x1050x1050
Net dimension grille (H./W./D.)	mm	48x860x860
Net weight unit + grille	kg	36

The pressure levels of Technibel products conform to European standard EN 12102

Nominal conditions

⁽¹⁾ T. Air inlet: +27°C D.B./ + 19°C W.B.

T. Water inlet: +7°C

T. Water outlet: +12°C

⁽²⁾ T. Air inlet: +20°C

T. Water inlet: +50°C / same water flow rate (1)