

Product data sheet

Item No. 92.232.9904.2

Cable assembly GST18I3K1-S 15E 99WS

geis® Connection cable male - free end; length: 9,9m; type GST18I3; 3-p ole; 250 V / 16 A; colour of coding: white with white strain-relief; cable: H05VV-F 3G1,5, colour: white, fire class Eca



Item No.	92.232.9904.2
EAN	4015573358737
Order Unit	5 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	16 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Code 1
Lockable	Yes
Color of coding/ contact carrier	White
Marking of poles	L, N, PE
Color of housing inclusive strain relief	White

Model

Nominal cross section conductor	1.5 mm <sup>2</sup>
Degree of protection (IP)	IP20
Wire strip length	9 mm
sheath strip length	37 mm
Preparation of conductor ends	Ultrasonically compressed wire ends
Cable type	H05VV-F
Cable colour	White

Cable diameter	8.3 mm
Version of cable	Male - free end
Type of cord set	Connection cable
Version cable end 1	GST18i3 plug
Version cable end 2	Free end

**Material**

Surface finish	Tin-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C
Fire class	Eca

**Dimensions**

Total length	10 m
--------------	------

**Technical drawing**

.F	Farbe colour	Codierung Stecker male	Kabelfarbe cable colour
.1	schwarz black	L R E N	schwarz black
.2	weiß white	L R E N	weiß white
.3	grau grey	L R E N	schwarz black
.5	rot red	L R E N	schwarz black

Kabel/cable H05VV-F3G1,5  
Farbe/color: siehe Tabelle/see table

Teile-Nr. part-no.	L	Beispiel (Farbe: schwarz) example (colour: black)	Typ type
92.232.XX04.F	XX in dm-Schritten	92.232.1004.1 = 10dm/L= 1000mm	GST18i3K1-S 15 10SW
U2.232.XX04.F	XX in m-Schritten	U2.232.1204.1 = 12 m/L=12000mm	GST18i3K1-S 15 X12SW

Typ/type: GST18i3K1-S 15 ..  
 SW = schwarz/black  
 WS = weiß/white  
 GR01 = grau/grey  
 RT03 = rot/red

Freitoleranz nach Serial tolerance		CD - Zeichnung, keine manuellen Änderungen CD - Drawing, no manual modifications allowed	1. Sendung - First Issue	Stück / no. 1
1	CD	2004	1	1
2	CD	14.09.	1	1
3	CD	14.09.	1	1
4	CD	14.09.	1	1
5	CD	14.09.	1	1
6	CD	14.09.	1	1

Weitere Daten siehe Katalog  
further data see catalog

**INSTALL COUPLER**  
**KONFEKT LEITUNG**  
 Stecker/male = 15mm Ende/free end 1.5mm  
 Crimpanschlussschraubung/crimpersion A1 250V