

## RFF 1/2" FLEXIBLE COAXIAL CABLE

### NK CODES

**RFF 1/2"-50**  
**RFF 1/2"-50 GHF**  
**RFF 1/2"-50 BHF**  
**RFF 1/2"-50 BHF (UL) CATVR**

**NKRFF01200**  
**NKRFF01201**  
**NKRFF01202**  
**NKRFF01204**

### CONSTRUCTION



Inner conductor	Copper-clad aluminium wire	Ø 3.55 mm (0.14 in)
Dielectric	Cellular polyethylene	Ø 9.0 mm (0.35 in)
Outer conductor	Corrugated copper tube	Ø 11.9 mm (0.47 in)
Jacket	See Jacketing Options table below	Ø 13.5 mm (0.53 in)
Marking	Draka, cable type, manufacture week, year, batch number and meter mark	

### ELECTRICAL CHARACTERISTICS at +20°C (+68°F)

Characteristic impedance	50 ± 1 Ω
Return loss 24 dB for 100 m cable with NKC connectors	
- 380 - 500	MHz
- 806 - 960	"
- 1710 - 1880	"
- 1900 - 2170	"
Other bands also available on request	
Bands according to customer's specifications	
Attenuation	See table
Velocity factor	0.82
Capacitance	82 pF/m (25 pF/ft)
Maximum frequency	12 500 MHz
Max power rating	See table
Peak RF voltage rating	1.39 kV
Peak power rating	19.0 kW
DC-resistance	
- Inner conductor	2.57 Ω/km (0.78 Ω/1000 ft)
- Outer conductor	3.10 Ω/km (0.94 Ω/1000 ft)

### MECHANICAL CHARACTERISTICS

Weight	0.19 kg/m (0.13 lb/ft)
Maximum pulling force	900 N (198 lb)
Minimum bending radius	
- Single bending	15 mm (0.6 in)
- Repeated bending	30 mm (1.2 in)
Operating temperature range	-55...+80°C (-67...+176 °F)
Crush resistance	3.4 kg/mm (190 lb/in)
Bending moment	2.7 Nm (2.0 lb-ft)
Recommended clamp distance	1.0 m (3.3 ft)

**JACKETING OPTIONS**

TYPE	JACKET	IEC60754-2 halogen free, non corrosive	IEC61034 low smoke emission	IEC60332 -3-24 fire retardant	UV retardancy	UL rated	Min. installation temperature
RFF 1/2"-50	Black, halogen free polyethylene	yes	no	no	yes	no	-40°C (-40°F)
RFF 1/2"-50 GHF	Grey, halogen free fire retardant thermoplastic	yes	yes	yes	no	no	-20°C (-4°F)
RFF 1/2"-50 BHF	Black, halogen free fire retardant thermoplastic	yes	yes	yes	yes	no	-20°C (-4°F)
RFF 1/2"-50 BHF (UL) CATVR	Black, halogen free fire retardant UL Riser rated jacket	yes	yes	yes	yes	yes	-20°C (-4°F)

**RFF 1/2" FLEXIBLE COAXIAL CABLE**

FREQUENCY MHz	ATTENUATION dB/100 m	ATTENUATION dB/100 ft	POWER RATING kW
10	0.972	0.296	8.4
30	1.70	0.517	4.8
50	2.20	0.671	3.7
88	2.94	0.896	2.7
100	3.14	0.957	2.6
108	3.27	0.996	2.5
174	4.18	1.28	1.9
200	4.50	1.37	1.8
300	5.56	1.70	1.4
400	6.48	1.97	1.2
450	6.89	2.10	1.2
500	7.29	2.22	1.1
512	7.38	2.25	1.1
600	8.04	2.45	0.99
700	8.73	2.66	0.91
800	9.38	2.86	0.85
850	9.70	2.96	0.82
890	9.94	3.03	0.80
900	10.0	3.05	0.79
950	10.3	3.14	0.77
960	10.4	3.16	0.77
1000	10.6	3.23	0.75
1200	11.7	3.57	0.68
1400	12.7	3.88	0.62
1600	13.7	4.18	0.58
1800	14.7	4.47	0.54
1900	15.1	4.60	0.52
2000	15.5	4.74	0.51
2200	16.4	5.00	0.48
2400	17.2	5.25	0.46
2600	18.0	5.50	0.44
2800	18.8	5.73	0.42
3000	19.6	5.97	0.40
3400	21.0	6.41	0.37
4000	23.1	7.05	0.34
6000	29.4	8.95	0.27
8000	35.0	10.7	0.22
12400	45.9	14.0	0.17

Attenuation values are typical at ambient temperature +20°C (+68°F).

Power rating ambient temperature +40°C (+104°F), inner conductor +100°C (+212°F).

**CODES FOR NKC CONNECTORS**

<b>CONNECTOR TYPE</b>	<b>NK CODE</b>
N male	NKC2012300
N female	NKC2012400
7-16 male	NKC2012100
7-16 female	NKC2012200
N male Right angle	NKC2012600
7-16 male Right angle	NKC2012500

© PRYSMIAN GROUP 2014, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group: any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.