

CERTIFICATE OF CONFORMITY

Cable type: **FLEXIDRUM T 210**

We confirm that the above mentioned cable is produced according to:

Conductor construction acc. to IEC 60228, DIN VDE 0295;

Color cores acc. to EN 50334;

Oil resistant acc. to IEC 60811-2-1, DIN VDE 0473 part.811-2-1;

Halogen free acc. to IEC 60754-1, DIN VDE 0482 part.267-1, EN 50267-1

Flame retardant acc. to IEC 60332-1, DIN VDE 0482 part.265-2-1, EN 50265-2-1, UL VW-1, CSA FT-1, CSA FT-2;

UL STYLE 21223 80°C 600/1000 V

Temperature range:**DIN VDE****UL/CSA**

-Fixed installation:

-50°C up to +90°C

+80°C

-Flexible installation:

-40°C up to +90°C

Nominal voltage:**DIN VDE****UL/CSA**

-U₀/U:

0,6/1 kV

600/1000 V

acc. to RoHS-guideline 2002/95/EG as well as GefStoffV appendix IV-no. 24
CE: The product is conformed with the EC Low-Voltage Directive 2006/95/EC

WARRANTY PERIOD:

The warranty period is 24 months after delivery

Operator	Technical manager
 Andrea Fiorini	 Luca Bolondi