

Cap. Soc. €uro 5.900.000 i.v. - CCIAA REA BG n. 280471 - Reg. Imp. BG 48525 - COD. ISO IT / P.I. / Cod. F. 02325450167
Sede Legale e Stabilimento BOLGARE: Via Francesca, 8 - 24060 Bolgare (BG) - ITALY - Tel. 035 4493011 – Fax 035 843131
Fax Uffici Commerciali 035 4493097 - e-mail info@icc.it - www.icc.it

TECHNICAL DATA SHEET N.° 2018-038

CABLE H05RN-F 3X1 mm²

Descriptions	Specifications
ICC Code	D2187000D
Designation	H05RN-F
Nominal size mm ²	3X1
Conductor	flexible bare copper class 5 EN 60228
Max diameter of wires in conductor	0.21 mm
Max conductor resistance at 20°C	19.5 Ohm/Km
Core diameter	2.45±0.1 mm
Average insulation thickness	0.6 mm
Minimum insulation thickness	0.44 mm
Insulation material	Rubber type EI4 EN 50363
Outer cable diameter	6.95±0.3 mm
Average sheath thickness	0.9 mm
Minimum sheath thickness	0.66 mm
Sheath material	Rubber type EM2 EN 50363
Marks	ICC IEMMEQU <HAR> H05RN-F 3X1 mm ² MADE IN ITALY
Standard	EN 50525-2-21
Rated voltage U ₀ /U	300/500 V
Max operating temperature	-25 / +60°C (on the conductor)
Insulation colour	Blue – Brown- Black
Sheath colour	Black

Further details. drawings or other specs.

- RoHS compliant