

CERTIFICATE OF CONFORMITYCable type: **GAALFLEX CONTROL 600**

We confirm that the above mentioned cable is produced according to:

Conductor construction: acc. to IEC 60228, DIN VDE 0295;

Cores color: acc. to EN50334

Flame retardant and self-extinguishing: acc. to IEC60332-1, DIN VDE 0482 part.265-2-1,
EN 50265-2-1, UL VW-1, CSA FT-1, FT-2;

Oil resistant: acc. to DIN EN 50290-2-22 resp. VDE 0819-102, TM54.

UL Style 2587 90°C 600 V or UL 21179 105°C 600 V

(on request 21216 90°C Oil 60°C 600V),

CSA AWM I/II A/B 90°C 600 V FT-1, FT-2

Temperature range:



	DIN VDE	UL/CSA
-Fixed installation:	-40°C up to +70°C	up to +90°C
-Flexible installation:	+5°C up to +70°C	up to +90°C

Nominal voltage:

	DIN VDE	UL/CSA
-U ₀ /U:	300/500 V	600 V

acc. to RoHS-guideline 2002/95/EG as well as GefStoffV appendix IV-no. 24
CE: The product is conformed with the EC Low-Voltage Directive 2006/95/EC**WARRANTY PERIOD:**

The warranty period is 24 months after delivery

Operator	Technical manager
 Andrea Fiorini	 Luca Bolondi