



## Product Data Sheet

# TIR-600

These cameras are attractive and easy to install. They are waterproof and automatically switch on built-in miniature LEDs when light levels drop to illuminate the area within the field of view.

Designed for easy installation, the bullet camera includes a mounting bracket and power supply. The TIR-600 has 330 lines of resolution, high sensitivity (0.5 lux) and advanced digital signal processing.

With a built-in IR illuminator, the camera also offers 0 lux with IR LEDs. In this mode, the effective distance is 10 meters.

### Standard Features

- Mounts on wall or ceiling
- Light grey aluminium waterproof housing
- Good sensitivity
- Adjustable camera position
- Standard resolution colour
- Automatic light sensor to illuminate built-in LEDs
- Complete with 12 VDC power supply and bracket

# TIR-600

## Specifications

Image sensor	1/3 in. CCD sensor
Horizontal resolution	330 TVL
Lens	6 mm / F2.5
Electronic shutter	1/3 ~ 1/10000 sec.
Sensitivity	0.5 lux or 0 lux under IR illumination
Gamma	0.45
Video out	Composite: 1 V pk-pk at 75 ohm load
Power supply	12 VDC (PSU incl.)
Power	2.2 W (IR LED off) and 3.72 W (IR LED on)
Effective distance with LEDs	10 m
IP rating	IP68
Operating temperature	-10 to +50°C
Dimensions	105 x 65 x 62 mm
Weight	640 g

## Ordering Information

Part No.	Description
TIR-600	330 TVL day/night, IP68, 6mm, built-in LED illuminators
TIR-300	330 TVL day/night, IP65, 3.6mm, built-in LED illuminators
TIR-400	330 TVL day/night, IP68, 4mm, built-in LED illuminators

