

ATS Heavy-duty Smart Card Reader

ATS1192

**ATS Heavy-duty Smart card reader with 2.5m cable**  
The ATS1192 smart card reader connect directly on the RS485 data bus of the control panel or 4-Door Controller and may be configured and addressed via a LCD keypad. Some security options (Site code & 4-byte security code) are only programmable via TITAN and configuration cards. The ATS1192 is mainly used for outdoor applications and due to the waterproof construction it is suitable for use in harsh environments.

Specifications

Supply voltage	9 - 14 V
Current consumption	25 - 80 mA
Open collector output	1(25 mA max)
"Request to exit" input	Yes
Max. distance from panel	1.5 km
Max. number per panel bus	16
Specified cable	Aritech WCAT 52/54 or equivalent
Data bus monitoring	Continuously monitored for offline condition of all devices on data bus
Addressing	Via keypad, TITAN or config. card
IP rating	IP54
Dimensions (W x H x D)	42 x 150 x 16 mm
Operating temperature	-35 to +66°C
Colour	Dark grey
Programmable OC output	pulse from 1 msec to 2.5 secs time from 1 sec to 193 days latch
Connectivity	RS485 data bus device or standard Wiegand for connection on the 4 reader inputs of the ATS1250
Read range (cm)	6 - 10
Optical pry-off tamper sensor	Yes
Epoxy-filled weatherproof construction	Yes
Red & Blue LEDs	Configurable as nightlight, lock status or alarm area status



- Full epoxy filled weather proof construction
- Heavy-duty version

Ordering Information

ATS1192	ATS Heavy-duty Smart Card Reader
ATS1471	ATS keyfob
ATS1475	ATS proximity card, packed by 10 pcs.
ATS1476	ATS proximity card, with Magstripe,
ATS1477	ATS fibertag.