


## VSG 42

Stop end, polyamide, RAL 7035, Pg42



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.



<b>Material</b>	Polyamide, fibre reinforced
<b>Temp. range min</b>	-40 °C
<b>Temp. range max</b>	100 °C
<b>Protection class</b>	IP56
<b>Advice</b>	with sealing IP66/IP68
<b>Thread type</b>	PG
<b>Ø Connection thread D</b>	42
<b>Length screw-in thread L</b>	10 mm
<b>Total length TL</b>	16 mm
<b>External diameter ED</b>	62 mm
<b>Product Color</b>	RAL 7035
<b>Order no. RAL 7035</b>	50060736
<b>Type</b>	VSG 42
<b>Packing unit</b>	25
<b>ETIM-Classification</b>	EC000032

### Recommended accessories

<b>MUG 42</b>	10060678
<b>ADR 42</b>	10061427

08.02.2021

Your Contact:

**WISKA Hoppmann GmbH**

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com



Your Contact:

**WISKA Hoppmann GmbH**

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com