



**YDPU2.E345553**  
**Tubing, Extruded Insulating - Component**

[Page Bottom](#)

**Tubing, Extruded Insulating - Component**

[See General Information for Tubing, Extruded Insulating - Component](#)

**SHENZHEN JDD TECH NEW MATERIAL CO LTD**

E345553

Bldg 2 E Zone  
 Minzhu Western Industrial Area  
 Shajing Town Baoan Dist  
 Shenzhen, Guangdong 518104 CHINA

Cat. No.	Max V	Max Temp C	Col Recognized	Max Temp Rated Oil Resistance C	VW-1 Rated#
<b>Flexible Heat-Shrinkable Polyolefin Tubing</b>					
MRS G	600	125	All except Clear	None	Yes
MCBG	300	125	All except Clear	None	Yes
<b>Not Heat-Shrinkable PTFE Tubing</b>					
MTFL	600	200	Natural	None	Yes
<b>Heat-Shrinkable Polyolefin Tubing with Meltable Liner</b>					
MSBG	600	125	All except Clear	None	Yes
<b>Not Heat-Shrinkable Standard Wall Silicone Tubing</b>					
MGJG	600	150	White	None	@
<b>Heat shrinkable flexible polyolefin tubing</b>					
RSG	600	125	All except clear	None	Yes
CBG	300	125	All except clear	None	Yes

# - Tubing is considered to comply with the optional VW-1 flammability requirements only if it is so marked for tubing authorized below.

@ - VW-1 rated for internal diameter sizes 6.50 - 15.00 mm only.

Marking: Company name or file number "E345553", catalog number, voltage rating, temperature rating in degrees C, inside diameter (before and after recovery), and date of manufacture shall be marked on tags attached to both ends of the tubing, on the shipping spool label or on the smallest unit container.

[Last Updated](#) on 2015-10-16

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2015 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2015 UL LLC".