



AU3.2

Nimi: **Kojerasia**
Irtonysärasia

Tyyppi: AU3.2
EAN: 6410011523643
Snro: 1152364

Kuvaus: Rasian sivuilla on 5 kpl nysäihioita, joista kaksi on samalla sivulla vierekkäin. Pohjaan voidaan liittää kaksi pohjanysää. Rasiat yhdistetään toisiinsa yhdyskappaleella PMR474. Valmistettu halogeenittomasta materiaalista (IEC/61249-2-21) ja täyttää hehkulankatestin vaatimukset standardin IEC/EN60670: 2005 (850 °C) mukaan.

Pakkaus: 100
Yksikkö: KPL



Tekniset tiedot

Sähkösuureet

Käyttöjännite 400 V

Lämpöolosuhteet

Käyttölämpötila -25 ... 90 °C

ETIM

ETIM 7 EC002601 (EC002601)

ETIM 8 EC002601 (EC002601)

ETIM 8

Mounting method Flush mounted (plaster)
Shape Round
Construction type Device connection box (round/square)
Model Single
Provided with revolving ring no
Connectable yes
Equipped with None
Diameter 71 mm
Depth 47 mm
Internal depth 45 mm
Suitable for wall/board thickness 12 ... 24 mm
For number of electric fittings 1

AU3.2

Mounting switching equipment	Screwing
With screws	yes
Housing feed-through by break-out opening	no
Housing feed-through by seal membrane	no
Housing feed-through by nozzle	no
Housing feed-through by step membrane	no
For tube diameter	20/25 mm
Pipe locking	yes
Pipe locking optional	no
Inlet from the rear	yes
Number of inlets	
Number of included spouts	
Material	Plastic
Halogen free	yes
Surface protection	Untreated
Colour	White
Degree of protection (IP)	Other
Transparent cover	no
Cover attachment	Snapped on
Sealable	no
Circuit integrity	None
With screening	no
Air tight	no
Max. conductor cross section	0 mm ²
Number of poles of the clamp	
Clamp position fixed	no
Luminaire hook mounting	no
Nozzle	None
With nail lugs	yes
Special application	None