

Product Information

Name: Surface Mounting Junction Box IP65

Technical Data: 400VAC

Rated Connecting Cap:

233: 2.5mm² 434: 6 mm²

Frequency: 50Hz

Colour: White

Main material: PP (Halogen free)

IP-Class: IP65

Working temperature: -25°C to +60°C

Installation temperature: -5°C to +25°C

Fire hazard test: 650°C (IEC60695-2-11)

The product complies with the standard(s): IEC60670-1, IEC60670-22

The product is in conformity with the provisions of the following European directive(s): LVD, RoHS, WEEE

Certificate(s): CE

Technical info:

The square junction box is equipped with 12 membrane cable entries on the sides, and two on the bottom. Cables are easy to be connected by simply inserting the stripped ends through the inlets. The box locked by snapping which can be opened by inserting a screwdriver (for example) into the opening slots - no screws are needed. The box can be furnished with the strain-reliefs on the center pin. Surface mounting.

The minimum and maximum temperatures during installation: -5°C to + 60°C.

Special strain relief is available for order. It can be used when connected in heavy cable, such as rubber cables: 3x1.5mm², 5x2.5mm².



E-No.	Type	Description/Remark
	G434	Junction box IP65, 105*105*46, without center pin and terminal

Drawing

