

Obico IP65

OBICO IP65 740LM 2CCT DIM ADJ WHT

0005350



Product features

- Integrated LED recessed spotlight, 2-axis adjustable (horizontal rotation 360°, vertical tilt 30°)
RAL9016 white bezel colour, two temperature light colors selectable: 3000K, 4000K. Lumen output 740lm (4000K), 8.5W, dimmable trailing/leading edge, 38° degree beam angle, aluminium and steel body, low profile 40mm recessed depth, IP65 frontal degree, IK03, loop-in/loop-out terminals for fast wiring, 96mm bezel diameter, 80mm cutout, clear lens.



PRODUCT OVERVIEW

Product name	OBICO IP65 740LM 2CCT DIM ADJ WHT
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
General application	Hospitality
ETIM Class	EC001744
E-number FI	4278283
Warranty	5 years
Fixture luminous flux (lm)	740
Luminaire efficacy (lm/W)	87
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	38
Photobiological Risk Group	RG1
Total power consumption (W)	8.5
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	Yes
Housing colour	White
IP rating	IP65/20
IK rating	IK03
Product EAN number	5410288053509

DATA TABLE

General data

Product name	OBICO IP65 740LM 2CCT DIM ADJ WHT
Technology	LED
Cap/Base	N/A

Obico IP65

OBICO IP65 740LM 2CCT DIM ADJ WHT

0005350

Housing	Aluminium
Mount	Ceiling recessed mounting
General application	Hospitality
Operating temperature range (°C)	-20°C - 40°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001744
E-number FI	4278283
Warranty	5 years

Optical data

Fixture luminous flux (lm)	740
Luminaire efficacy (lm/W)	87
Colour temperature (K)	4000
Correlated colour temperature range (K)	3000 - 4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	38
Distribution type	Direct
Photobiological Risk Group	RG1

Electrical data

Total power consumption (W)	8.5
Mains voltage (V)	220-240V~
Lamp power factor	1
THD (at 230 V, 50 Hz, full load, at 100% dimming level) xx.x %	25
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	Yes
Drive current (mA)	185
Inrush Current (A)	2
Inrush Duration (µs)	20
Glow Wire Test (°C)	650
Energy Efficiency Class (A->G) of contained light source	D
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	90
Max. Luminaires per 13A C Breaker	118
Max. Luminaires per 16A C Breaker	145
Max. Luminaires per 20A C Breaker	181
Max. Luminaires per 10A B Breaker	90
Max. Luminaires per 13A B Breaker	118
Max. Luminaires per 16A B Breaker	145
Max. Luminaires per 20A B Breaker	181

Lifetime data

Lifespan L70 B50	82000
------------------	-------

Obico IP65

OBICO IP65 740LM 2CCT DIM ADJ WHT

0005350

Physical data

Housing colour	White
IP rating	IP65/20
IK rating	IK03
Diffuser finish	Other
Diffuser material	PC Polycarbonate
Reflector finish	None
Nominal Product Height (mm)	40
Nominal Product Diameter (mm)	96
Cutout Dimensions (W x L in mm or Diameter in mm)	80
Weight (kg)	0.25



Packaging

Single packaging type	Carton
Product EAN number	5410288053509
Packaging single length / height (cm)	13.1
Packaging single width (cm)	8.0
Packaging single depth (cm)	14.4
DUN14 (inner)	25410288053503
Units per inner package	4
Packaging inner length / height (cm)	33.8
Packaging inner width (cm)	15.4
Packaging inner depth (cm)	14.5
DUN14 (outer)	15410288053506
Units per outer package	6
Packaging outer length / height (cm)	35.5
Packaging outer width (cm)	32.5
Packaging outer depth (cm)	46.2

Safety data

Optimal operating condition (°C)	-20-40
----------------------------------	--------

PHOTOMETRY



Obico IP65

OBICO IP65 740LM 2CCT DIM ADJ WHT

0005350

TECHNICAL DRAWINGS

