



TECHNICAL FOLDER

FILTERCEL HT5

Specifications

Code	H512244
Name	HT5
Description	PLEATED FILTER CELL

Applications

Spray booths and paint drying oven filtration. Pre-filtration and filtration with temperature up to 300°C.

Sizes

dimensions	287x592x98	mm
------------	------------	----

Technical data

filter medium composition	glass microfiber
frame material	galvanized sheet
regeneration	no
max. working temperature	300 °C
max. working R.H.	90 %

Funcional data

nominal air flow	860	m ³ /h
initial pressure drop	35	Pa
final pressure drop	300	Pa
colorimetric efficiency	55	%
classification (EN 779:2012)	M5	
classification (ISO 16890)	ePM10 65	%
flame resistance	2 (U.L.)	

Rev 00_19

GENERAL FILTER HEADQUARTER

Via Emilia, 23
31038 Paese (TV), Italia
Tel: +39 0422 4594
Fax: +39 0422 459590
www.generalfilter.com
info@generalfilter.com

GENERAL FILTER ITALIA

Via Morgagni, 40 int. 7/8
20010 Pogliano Milanese (MI), Italia
Tel: +39 02 93550640
Fax: +39 02 93255670
Italia: sales.ita@generalfilter.com
Estero: sales.int@generalfilter.com

GENERAL FILTER FRANCE

13 Avenue d'Aygu
26200 Montlimar, France
Tel: +33 987876598
Fax: +33 987876599
r.meucci@generalfilter.fr

GENERAL FILTER IBERICA

C/Cabo Ortegá, nrs. 3-5 LA POVEDA
28500 Arganda del Rey, Madrid,
España
Tel: +34 91 8719046
Fax: +34 91 8719054
gefisa@generalfilter.com

GENERAL FILTER HAVAK

Sanayi Sitesi P. Blok No. 10
Hosdere Mevkii
34517 Esenyurt, Istanbul, Türkiye
Tel: +90 212 623 0074
Fax: +90 212 623 0075
info@generalfilterhavak.com