

NLE11KK.2

Energy-optimized Compressor

R600a

220-240V 50Hz

Data Sheet (Replaces CD.53.F1.02)

General

Compressor	NLE11KK.2
Code number	105H6950

Application

Application		LBP
Evaporating temperature range	°C	-35 to -10
Voltage range	V/Hz	198 - 254 /50
Motor type		RSIR/RSCR
Max. ambient temperature	°C	38
Comp. cooling at ambient temp.	32°C	S
	38°C	S

Design


Displacement	cm ³	11.15
Oil quantity	cm ³	270
Maximum refrigerant charge	g	150
Free gas vol. in compressor	cm ³	2310
Weight without electrical equipment	kg	10.0

Motor


Motor size	watt	140
LRA (rated after 4 sec. UL984) LST	A	5.0
Cut-in current LST	A	9.4
Resistance, main and start winding (25°C)	Ω	14.9/17.9
Approvals		EN 60335-2-34 with Annex AA

Dimensions

Height	mm	A	197
		B	191
Suction connector	location/I.D. mm	C	6.2 ±0.09
Process connector	location/I.D. mm	D	6.2 ±0.09
Discharge connector	location/I.D. mm	E	5.0 +0.12/+0.20
Compressors on a pallet	pcs.		80



- S = Static cooling normally sufficient
- O = Oil cooling
- F₁ = Fan cooling 1.5 m/s
(compressor compartment temperature equal to ambient temperature)
- F₂ = Fan cooling 3.0 m/s necessary



Capacity (EN 12900/CECOMAF)**watt**

Comp.°C	-35	-30	-25	-23.3	-20	-15	-10
NLE11KK.2	78	103	133	144	169	214	271

Capacity (ASHRAE)**watt**

Comp.°C	-35	-30	-25	-23.3	-20	-15	-10
NLE11KK.2	94	126	162	175	206	261	330

Power consumption**watt**

Comp.°C	-35	-30	-25	-23.3	-20	-15	-10
NLE11KK.2	86	103	119	124	135	153	173

Current consumption**A**

Comp.°C	-35	-30	-25	-23.3	-20	-15	-10
NLE11KK.2	0.70	0.74	0.80	0.81	0.85	0.90	0.96

COP (EN 12900/CECOMAF)**W/W**

Comp.°C	-35	-30	-25	-23.3	-20	-15	-10
NLE11KK.2	0.90	1.01	1.12	1.16	1.25	1.40	1.57

COP (ASHRAE)**W/W**

Comp.°C	-35	-30	-25	-23.3	-20	-15	-10
NLE11KK.2	1.10	1.22	1.36	1.41	1.52	1.70	1.91

Test conditions

EN 12900/CECOMAF

ASHRAE

Condensing temperature

55°C

55°C

Ambient and suction gas temp.

32°C

32°C

Liquid temperature

55°C

32°C

Static cooling, 220V 50Hz,

PTC consumption incl.

Accessories

Devices	Fig.	NLE11KK.2
PTC starting device 6.3 mm spades	a1	103N0011
4.8 mm spades	(pos.1)	103N0018
PTC starting device 6.3 mm spades	a1	103N0016
4.8 mm spades	(pos.2)	103N0021
Cover	b	103N2010
Cord relief	d	103N1010
Run capacitor 4 µF (optional)	e	117-7117
6.3 mm spades		117-7119
4.8 mm spades		
Protection screen for PTC	g	103N0476
Mounting accessories		
Bolt joint for one compressor		118-1917
Bolt joint in quantities		118-1918
Snap-on in quantities		118-1919

