

Kontaktoreiden vertailutaulukko

AC-kuormitusluokat alle 40 °C lämpötila (koteloitu)

	Danfoss	ABB	Siemens	Klöc-M.	Telemeq.	Lovato	AEG
4kW	CI 4-9	B6-30	3TG10	DIL EM	LC1-K09	MC9	LS 07
AC-1/A	25	20	20	16	20	16	16
AC-3/A	9	9	8,4	9	9	9	7
leveys/mm	45	50	36	45	45	45	45
korkeus/mm	47	50	62	58	58	48	40
syvyys/mm	48	47	60	52	57	55	45
apukosketin	S tai A	S tai A	S tai A	S tai A	S tai A	S tai A	S tai A
4kW	CI 9	A 9	3RT1016	DIL 00M	LC1-D09	BF9	LS 4K
AC-1/A	25	25	20	16	25	25	25
AC-3/A	9	9	9	9	9	9	9
leveys/mm	44	44	45	45	45	45	45
korkeus/mm	72	74	58	77	82	80	81
syvyys/mm	77	74	67	74	90	80	85
apukosketin	ei	S tai A	S tai A	ei	S tai A	S tai A	S tai A
5,5kW	CI 12	A 12	3RT1017	DIL 00AM	LC1-D12	BF12	LS 5K
AC-1/A	25	27	20	16	25	25	25
AC-3/A	12	12	12	12	12	12	12
leveys/mm	44	44	45	45	45	45	45
korkeus/mm	72	74	58	77	82	80	81
syvyys/mm	77	74	67	74	90	80	85
apukosketin	ei	S tai A	S tai A	ei	S tai A	S tai A	S tai A
7,5kW	CI 16	A 16	3RT1025	DIL 0M	LC1-D18	BF16	LS 7K
AC-1/A	40	30	35	30	32	25	32
AC-3/A	16	17	17	16	18	16	16
leveys/mm	55	44	45	45	45	45	45
korkeus/mm	75	74	58	91	87	80	81
syvyys/mm	77	74	67	79	95	80	85
apukosketin	ei	S tai A	ei	ei	S tai A	S tai A	S tai A
11kW	CI 25	A 26	3RT1026	DIL 0AM	LC1-D25	BF25	LS 11K
AC-1/A	40	45	35	30	40	40	45
AC-3/A	25	26	25	25	25	25	25
leveys/mm	55	54	45	45	57	45	45
korkeus/mm	75	90	80	91	95	83	81
syvyys/mm	77	94	91	79	103	85	87
apukosketin	ei	S tai A	ei	ei	S tai A	ei	ei
15kW	CI 32	A 30	3RT1034	DIL 1M	LC1-D32	BF32	LS 15K
AC-1/A	63	55	45	44	50		60
AC-3/A	32	32	32	32	32	32	32
leveys/mm	75	54	55	60	57	55	55
korkeus/mm	90	90	105	98	84	88	87
syvyys/mm	96	108	115	97	108	91	98
apukosketin	ei	S tai A	ei	ei	S tai A	ei	ei

18,5kW	CI 37	A 40	3RT1035	DIL 1AM	LC1-D38	BF38	LS 18K
AC-1/A	80	60	55	44	50	60	90
AC-3/A	37	37	40	37	38	38	37
leveys/mm	75	54	55	60	57	55	55
korkeus/mm	90	90	105	98	84	88	87
syvyys/mm	96	108	115	97	108	91	98
apukosketin	ei	S tai A	ei	ei	S tai A	ei	ei

22kW	CI 45	A 50	3RT1036	DIL 2M	LC1-D50	BF 50	LS 22K
AC-1/A	80	100	50	80	80	90	90
AC-3/A	45	50	50	45	50	50	45
leveys/mm	75	70	55	70	60	75	66
korkeus/mm	90	110	105	118	127	124	118
syvyys/mm	96	108	115	102	121	107	116
apukosketin	ei	ei	ei	ei	S ja A	ei	ei

25kW	CI 50	A 63	3RT1044	DIL 2AM	LC1-D50	BF50	LS 30K
AC-1/A	80	115	90	80	80	90	110
AC-3/A	50	65	65	57	50	50	60
leveys/mm	75	70	70	70	60	75	66
korkeus/mm	90	110	140	118	127	124	118
syvyys/mm	96	108	139	102	121	107	116
apukosketin	ei	ei	ei	ei	S ja A	ei	ei

Lämpöreleet	TI 16-30C	TA 25	3RU1116	Z00	LR 2	11 RF25	B05
	CI 9-25	A9...A40	3RT1016-25	DIL0-0A	LC1-D09-38	BF9-BF38	LS 4-5K
leveys/mm	49	44	45	45	44	44	45
korkeus/mm	36	59	61	85	47	36	51
syvyys/mm	75	96	86	90	92	88	53

Lämpöreleet	TI 80	TA 42	3RU1126	Z1	LR 2	11 RF95	B18K
	CI 32-50	A30..A40	3RT1026	DIL1-2	LC1-D25-38	BF20-BF95	LS 4-18K
leveys/mm	81	54	45	60	54	55	45
korkeus/mm	57	65	97	86	59	55	85
syvyys/mm	88	112	86	102	92	105	98

Lämpöreleet		TA 75	3RU1136		LR 2		B 55K
		A50..A63	3RT1034-36		LC1-D50		LS 22-30K
leveys/mm		54	55		70		62
korkeus/mm		66	102		54		118
syvyys/mm		113	107		109		112

Lämpöreleet			3RU1146				
			3RT1044				
leveys/mm			45				
korkeus/mm			97				
syvyys/mm			86				