


KAHVASULAKKEET 500 V - gG/gL

Nimellisjännite: 500 VAC
Katkaisukyky: Min. 120 kA
Käyttöluokka: gG/gL
Normit: DIN 43 620/21
VDE 0636
IEC 269-1, EN 60269-1
Rakenne: Korroosiosuojattu



Koko 00

Tyyppi no.	kpl/pakkaus	Snro
20 000 13.2A	10	31 350 02
20 000 13.4A	10	31 350 04
20 000 13.6A	10	31 350 06
20 000 13.10A	10	31 350 10
20 000 13.16A	10	31 350 16
20 000 13.20A	10	31 350 20
20 000 13.25A	10	31 350 25
20 000 13.32A	10	
20 000 13.35A	10	31 350 35
20 000 13.40A	10	
20 000 13.50A	10	31 350 50
20 000 13.63A	10	31 350 63
20 000 13.80A	10	31 350 80
20 000 13.100A	10	31 350 81
20 001 13.125A	10	31 350 85
20 001 13.160A	10	31 350 86

Koko 0

20 002 13.100A	3	31 351 81
20 002 13.125A	3	31 351 85
20 002 13.160A	3	31 351 86
20 002 13.200A	3	31 351 90
20 002 13.250A	3	31 351 92

Koko 1

20 003 13.16A	3	31 352 16
20 003 13.20A	3	31 352 20
20 003 13.25A	3	31 352 25
20 003 13.35A	3	31 352 35
20 003 13.50A	3	31 352 50
20 003 13.63A	3	31 352 63
20 003 13.80A	3	31 352 80
20 003 13.100A	3	31 352 81
20 003 13.125A	3	31 352 85
20 003 13.160A	3	31 352 86
20 003 13.200A	3	31 352 90
20 003 13.224A	3	31 352 91
20 003 13.250A	3	31 352 92

Koko 2

Tyyppi no.	kpl/pakkaus	Snro
20 004 13.35A	3	31 353 35
20 004 13.50A	3	31 353 50
20 004 13.63A	3	31 353 60
20 004 13.80A	3	31 353 80
20 004 13.100A	3	31 353 81
20 004 13.125A	3	31 353 85
20 004 13.160A	3	31 353 86
20 004 13.200A	3	31 353 90
20 004 13.224A	3	31 353 91
20 004 13.250A	3	31 353 92
20 004 13.300A	3	31 353 93
20 004 13.315A	3	31 353 94
20 004 13.355A	3	31 353 95
20 004 13.400A	3	31 353 96

Koko 3

20 005 13.300A	3	31 354 30
20 005 13.315A	3	31 354 31
20 005 13.355A	3	31 354 35
20 005 13.400A	3	31 354 40
20 005 13.425A	3	31 354 42
20 005 13.500A	3	31 354 50
20 005 13.630A	3	31 354 63