


KAHVASULAKKEET

Nimellisjännite: 690 VAC
Katkaisukyky: Min. 120 kA
Käyttöluokka: aM
Normit: DIN 43 620, VDE 0636/22
Rakenne: Korroosiosuojattu



Koko 00

Tyyppi no.	kpl/pakkaus	Snro
20 477 08.2A	3	31 366 02
20 477 08.4A	3	31 366 04
20 477 08.6A	3	31 366 06
20 477 08.10A	3	31 366 10
20 477 08.16A	3	31 366 16
20 477 08.20A	3	31 366 20
20 477 08.25A	3	31 366 25
20 477 08.32A	3	31 366 32
20 477 08.35A	3	31 366 35
20 477 08.40A	3	31 366 40
20 477 08.50A	3	31 366 50
20 209 08.63A	3	31 366 63
20 209 08.80A	3	31 366 80
20 209 08.100A	3	31 366 81
20 209 08.125A	3	31 366 85

Koko 1

20 211 08.16A	3	31 368 16
20 211 08.20A	3	31 368 20
20 211 08.25A	3	31 368 25
20 211 08.35A	3	31 368 35
20 211 08.50A	3	31 368 50
20 211 08.63A	3	31 368 63
20 211 08.80A	3	31 368 80
20 211 08.100A	3	31 368 81
20 211 08.125A	3	31 368 85
20 211 08.160A	3	31 368 86
20 211 08.200A	3	31 368 90
20 211 08.250A	3	31 368 92

Toimitusohjelmassa myös 0-koko

Koko 2

Tyyppi no.	kpl/pakkaus	Snro
20 212 08.35A	3	31 369 35
20 212 08.50A	3	31 369 50
20 212 08.63A	3	31 369 63
20 212 08.80A	3	31 369 80
20 212 08.100A	3	31 369 81
20 212 08.125A	3	31 369 85
20 212 08.160A	3	31 369 86
20 212 08.200A	3	31 369 90
20 212 08.250A	3	31 369 92
20 212 08.300A	3	
20 212 08.315A	3	31 369 93
20 212 08.355A	3	31 369 95
20 212 08.400A	3	31 369 94

Koko 3

20 213 08.300A	3	
20 213 08.315A	3	31 370 31
20 213 08.355A	3	31 370 35
20 213 08.400A	3	31 370 40
20 213 08.425A	3	
20 213 08.500A	3	31 370 50
20 213 08.630A	3	31 370 63

Koko 4

20 225 08.400A	3	31 371 40
20 225 08.500A	3	31 371 50
20 225 08.630A	3	31 371 63
20 225 08.800A	3	31 371 80
20 225 08.1000A	3	31 371 90

Koko 4a

20 227 08.500A	3	31 348 50
20 227 08.630A	3	31 348 63
20 227 08.800A	3	31 348 80
20 227 08.1000A	3	31 348 90