

Kauluslaippa pyörivällä laipparengaalla PN 16 (asennusmitat DIN 2633 ja EN 1092-1 mukaiset)

Koodi	DN	laipparengas							Kpl	Koko	kaulusosa						
		d1	D	K	d	d5	a	b1			d2	d4	a1	a2	h1	s1	kg
0525552	15	21,3	95	65	38	25	3	11.5	4	M12	13.5	51.5	3.0	2.5	35	1.6	0.30
0525553	20	26,9	105	75	48	30	3	14.0	4	M12	13.5	61.5	3.0	2.5	38	1.6	0.40
0525554	25	33,7	115	85	53	38	3	16.0	4	M12	13.5	71.0	3.0	2.5	38	2.0	0.50
0525555	32	42,4	140	100	68	46	3	16.5	4	M16	17.5	82.5	3.0	2.5	40	2.0	0.70
0525556	40	48,3	150	110	77	54	4	18.0	4	M16	17.5	92.5	3.0	2.5	42	2.0	0.93
0525557	50	60,3	165	125	91	65	4	20.0	4	M16	17.5	107.5	3.5	2.5	45	2.0	1.30
0525558	65	76,1	185	145	108	81	5	22.0	4	M16	17.5	127.5	4.0	3.0	45	2.3	1.80
0525559	80	88,9	200	160	123	94	5	23.0	8	M16	17.5	142.5	3.5	3.0	50	2.3	2.00
0525560	100	114,3	220	180	141	119	6	24.0	8	M16	17.5	162.5	4.0	3.0	52	2.6	2.95
0525561	125	139,7	250	210	168	145	6	25.5	8	M16	17.5	192.0	4.0	3.5	55	2.6	3.50
0525562	150	168,3	285	240	192	173	6	27.0	8	M20	21.5	218.0	4.0	3.5	55	2.6	4.20
0525563	200	219,1	340	295	245	225	8	31.0	12	M20	21.5	273.0	5.0	4.5	62	2.9	7.35

Materiaali:

Kaulusosa EN 1.4404

Pyörivä laipparengas EN 1.4307

