

**SAK Series, Accessories**  
**Q 2 SAK4****Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

This type of cross-connection has a pre-assembled captive cross-connection lug, cross-connection sleeve and fixing screw.

All the individual parts are available separately on request. During installation, the pre-assembled cross-connectors are simply placed in the cross-connection slot in the middle of the terminal and screwed tight.

**General ordering data**

|            |  |
|------------|--|
| Type       | Q 2 SAK4   |
| Order No.  | <a href="#">0336700000</a>   |
| Version    | SAK Series, Accessories, Cross-connector, for cross-connection link, No. of poles: 2 |
| GTIN (EAN) | 4008190033842  |
| Qty.       | 50 pc(s).  |

**Data sheet**

**SAK Series, Accessories  
Q 2 SAK4**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data**

**Dimensions and weights**

|       |         |            |        |
|-------|---------|------------|--------|
| Width | 11 mm   | Height     | 6 mm   |
| Depth | 20.5 mm | Net weight | 4.82 g |

**Additional technical data**

|                          |                           |                     |                 |
|--------------------------|---------------------------|---------------------|-----------------|
| Explosion-tested version | No                        | Installation advice | Direct mounting |
| Version                  | for cross-connection link |                     |                 |

**Rated data**

|               |      |
|---------------|------|
| Rated current | 24 A |
|---------------|------|

**Material data**

|        |      |
|--------|------|
| Colour | Grey |
|--------|------|

**System specifications**

|                |                         |               |      |
|----------------|-------------------------|---------------|------|
| Product family | SAK Series, Accessories | Mounting rail | none |
|----------------|-------------------------|---------------|------|

**Classifications**

|            |             |            |             |
|------------|-------------|------------|-------------|
| ETIM 3.0   | EC000489    | UNSPSC     | 30-21-18-01 |
| eClass 5.1 | 27-14-11-40 | eClass 6.2 | 27-14-11-40 |
| eClass 7.1 | 27-14-11-40 |            |             |

**Product information**

|                                 |   |
|---------------------------------|---|
| Descriptive text technical data | Current-carrying capacity up to 41 A via the cross-connection, max. 6 mm <sup>2</sup> |
|---------------------------------|---|

**Approvals**

|           |   |
|-----------|---|
| Approvals |  |
|-----------|---|

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

**Downloads**

|      |   |
|------|---|
| STEP | <a href="#">0336700000_15308_Q_2_SAK4_STP.stp</a> |
|------|---|