

**Accessories**  
**ZQV 4/2 GE****Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

Weidmüller offers users of modular terminals of the Z-Series a comprehensive range of accessories that render possible appropriate solutions for all - even non-standard - tasks.

The accessories must comply with the same quality standards as the modular terminals themselves.

**General ordering data**

|            |                                    |
|------------|------------------------------------|
| Type       | ZQV 4/2 GE                         |
| Order No.  | <a href="#">1608950000</a>         |
| Version    | Accessories, Cross-connector, 32 A |
| GTIN (EAN) | 4008190263225                      |
| Qty.       | 60 pc(s).                          |

**Data sheet**

**Accessories  
ZQV 4/2 GE**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data**

**Dimensions and weights**

|       |         |            |         |
|-------|---------|------------|---------|
| Width | 2.8 mm  | Height     | 10.5 mm |
| Depth | 31.6 mm | Net weight | 1.619 g |

**Temperatures**

|                                  |        |                                  |        |
|----------------------------------|--------|----------------------------------|--------|
| Continuous operating temp., min. | -50 °C | Continuous operating temp., max. | 120 °C |
|----------------------------------|--------|----------------------------------|--------|

**Additional technical data**

|                          |                   |                     |                 |
|--------------------------|-------------------|---------------------|-----------------|
| Explosion-tested version | No                | Installation advice | Direct mounting |
| Version                  | For the terminals |                     |                 |

**Rated data**

|               |      |
|---------------|------|
| Rated current | 32 A |
|---------------|------|

**Material data**

|                           |       |        |        |
|---------------------------|-------|--------|--------|
| Material                  | Wemid | Colour | Yellow |
| UL 94 flammability rating | V-0   |        |        |

**System specifications**

|                |             |               |      |
|----------------|-------------|---------------|------|
| Product family | Accessories | Mounting rail | none |
|----------------|-------------|---------------|------|

**Classifications**

|            |             |            |             |
|------------|-------------|------------|-------------|
| ETIM 3.0   | EC000489    | UNSPSC     | 30-21-18-01 |
| eClass 5.1 | 27-14-11-40 | eClass 6.2 | 27-14-11-40 |
| eClass 7.1 | 27-14-11-40 |            |             |

**Approvals**

Approvals



|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|