

Product	Thermally operated control for appliances
Applicant	Safera Oy Muuntotie 1 FI-01510 Vantaa Finland
Manufacturer	Safera Oy Muuntotie 1 FI-01510 Vantaa Finland
Factory	Safera Oy Muuntotie 1 FI-01510 Vantaa Finland <input type="checkbox"/> See next page(s)
Ratings	3x10A for 400V delta load; 3x16A for 230V star load
Trade mark	SAFERA
Model / Type Ref.	PCU3
Principal characteristics	Cl. II, Type 1.B (micro-disconnection) 6000(A), IP65, Fixed wiring with flexible cables premounted. Independently surface mounted thermal cut-out for appliances (stoves). Pollution degree 2 and PTI 175V. Uimp: 2500V and category D. <input type="checkbox"/> See next page(s)
A sample of the product was tested and found to be in conformity with	CONT EN 60730-1:2000;A1;A12;A13;A14;A16;A2 EN 60730-2-9:2010
Validity	This certificate documents conformity with the standards shown, and also applies as license for use of Nemkos name and certification mark. The certificate and license is valid as long as the applicable conditions are complied with, and provided that any changes to the product are notified to Nemko for acceptance prior to implementation. New standards or amendments to the standards may imply that the product design must be updated and/or that re-testing and re-certification is necessary.
Additional information	<input type="checkbox"/> See next page(s)
Additional model(s)	<input checked="" type="checkbox"/> See next page(s)

Date of issue 01-10-2012



Signature

Hanne Yndestad

Certification Department

Nemko AS

Office address

Internet

Telephone

Fax

P.O. Box 73, Blindern

Gaustadalléen 30

www.nemko.com

+47 22 96 03 30

+ 47 22 96 05 50

N-0314 Oslo, Norway

Oslo

Enterprise number:

NO 974404532

Product	Thermally operated control for appliances
Pos. No	1
Model / Type Ref.	PCU5.1-P
Trade mark (if different from page 1)	
Rating	25A for 230V single phase load
Principal characteristics	Cl. I, Type 1.B (micro-disconnection) 6000(A), IP20, pillar terminals for fixed wiring and Norwesco socket outlet. Independently surface mounted thermal cut-out for appliance (stoves). Pollution degree 2 and PTI 175V. Uimp: 2500V and category D.
Product	Thermally operated control for appliances
Pos. No	2
Model / Type Ref.	PCU4.1-U
Trade mark (if different from page 1)	
Rating	25A for 230V single phase load
Principal characteristics	Cl. II, Type 1.B (micro-disconnection) 6000(A), IP44, Fixed wiring with flexible cables premounted. Independently surface mounted thermal cut-out for appliances (stoves). Pollution degree 2 and PTI 175V. Uimp: 2500V and category D.
Product	Thermally operated control for appliances
Pos. No	3
Model / Type Ref.	PCU3-W
Trade mark (if different from page 1)	
Rating	3x10A for 400V delta load; 3x16A for 230V star load
Principal characteristics	Cl. I, Type 1.B (micro-disconnection) 6000(A), IP20, perilex plug and socket outlet. Independently surface mounted thermal cut-out for appliance (stoves). Pollution degree 2 and PTI 175V. Uimp: 2500V and category D.

Date of issue 01-10-2012



Signature

Hanne Yndestad

Certification Department