



type		dimensions											bolt	loading ratings(N)				weight
SAP		ø d	H	L	J	A	N	N1	H1	H2	B	S	mm	dyn. C	stat. Co	bearing	housing	kg
ANQ899	UCP201	12	30,2	127	95	38	13	19	14	62	44,5	12,7	M10	12160	6318	UC201	P201	0,69
ANQ900	UCP202	15	30,2	127	95	38	13	19	14	62	44,5	12,7	M10	12160	6318	UC202	P203	0,69
ANQ901	UCP203	17	30,2	127	95	38	13	19	14	62	44,5	12,7	M10	12160	6318	UC203	P203	0,68
ANQ902	UCP204	20	33,3	127	95	38	13	19	14	65	44,5	12,7	M10	12160	6318	UC204	P204	0,66
ANQ903	UCP205	25	36,5	140	105	38	13	19	15	71	48	14,3	M10	13300	7457	UC205	P205	0,81
ANQ904	UCP206	30	42,9	165	121	48	17	20	17	84	53	15,9	M14	18525	10735	UC206	P206	1,24
ANQ905	UCP207	35	47,6	167	127	48	17	20	18	93	59,5	17,5	M14	24415	14630	UC207	P207	1,58
ANQ906	UCP208	40	49,2	184	137	54	17	20	18	100	69	19	M14	27645	16910	UC208	P208	1,89
ANQ907	UCP209	45	54	190	146	54	17	20	20	106	69	19	M14	32395	20235	UC209	P209	2,14
ANQ908	UCP210	50	57,2	206	159	60	20	23	21	113	74,5	19	M16	33345	22135	UC210	P210	2,66
ANQ909	UCP211	55	63,5	219	171	60	20	23	23	125	76	22,2	M16	41230	27930	UC211	P211	3,31
ANQ910	UCP212	60	69,8	241	184	70	20	23	25	138	89	25,4	M16	49780	34390	UC212	P212	4,9
ANQ911	UCP213	65	76,2	265	203	70	25	28	27	150	89	25,4	M20	54340	38095	UC213	P213	5,15
ANQ912	UCP214	70	79,4	266	210	72	25	28	27	156	-	30,2	M20	59090	41895	UC214	P214	6,2
ANQ913	UCP215	75	82,6	275	217	74	25	28	28	162	-	33,3	M20	64030	45885	UC215	P215	7,16
ANQ914	UCP216	80	88,9	292	232	78	25	28	30	174	-	33,3	M20	69065	50350	UC216	P216	8,1
ANQ915	UCP217	85	95,2	310	247	83	25	28	32	185	-	34,1	M20	79800	58805	UC217	P217	9,81
ANQ916	UCP218	90	101,6	327	262	88	27	30	33	198	-	39,7	M22	91295	67925	UC218	P218	11,96