



type		dimensions											bolt	loading ratings(N)			weight	
SAP		Ø d	H	L	J	A	N	N1	H1	H2	B	S	mm	dyn. C	stat. Co	bearing	housing	kg
ANQ987	UCP305	25	45	175	132	45	17	20	15	85	38	15	M14	20140	10355	UC305	P305	1,4
ANQ988	UCP306	30	50	180	140	50	17	20	18	95	43	17	M14	25365	14250	UC306	P306	1,8
ANQ989	UCP307	35	56	210	160	56	17	25	20	106	48	19	M14	31730	18335	UC307	P307	2,8
ANQ990	UCP308	40	60	220	170	60	17	27	22	116	52	19	M14	38665	22800	UC308	P308	3
ANQ991	UCP309	45	67	245	190	67	20	30	24	129	57	22	M16	46455	28025	UC309	P309	4,1
ANQ992	UCP310	50	75	275	212	75	20	35	27	143	61	22	M16	58900	36385	UC310	P310	5,8
ANQ993	UCP311	55	80	310	236	80	20	38	30	154	66	25	M16	68020	42750	UC311	P311	7,4
ANQ994	UCP312	60	85	330	250	85	25	38	32	165	71	26	M20	77805	49590	UC312	P312	9,4
ANQ995	UCP313	65	90	340	260	90	25	38	33	176	75	30	M20	88065	56905	UC313	P313	10
ANQ996	UCP314	70	95	360	280	90	27	40	35	187	78	33	M22	98800	64790	UC314	P314	12
ANQ997	UCP315	75	100	380	290	100	27	40	35	198	82	32	M22	107350	73340	UC315	P315	14
ANQ998	UCP316	80	106	400	300	110	27	40	40	210	86	34	M22	111850	82365	UC316	P316	18
*	UCP317	85	112	420	320	110	33	45	40	220	96	40	M27	126350	91960	UC317	P317	20
ANQ999	UCP318	90	118	430	330	110	33	45	45	235	96	40	M27	135850	101650	UC318	P318	24
*	UCP319	95	125	470	360	120	36	50	45	250	103	41	M30	145350	113050	UC319	P319	29
ANR001	UCP320	100	140	490	380	120	36	50	50	275	108	42	M30	164350	133950	UC320	P320	35
*	UCP321	105	140	490	380	120	36	50	56	283	112	44	M33	174800	145350	UC321	P321	35
*	UCP322	110	150	520	400	140	40	55	61	303	117	46	M33	194750	171000	UC322	P322	45
ANR002	UCP324	120	160	570	450	140	40	55	71	323	126	51	M33	196650	175750	UC324	P324	55
*	UCP326	130	180	600	480	140	40	55	81	363	135	54	M33	217550	203300	UC326	P326	72
*	UCP328	140	200	620	500	140	40	55	81	403	145	59	M33	240350	233700	UC328	P328	89