



SAP	type	dimensions										bolt mm	loads ratings(N)			weight	
		d	H	J	A2	A1	A	2-φN	B	A0	S		dyn. C	stat. C0	bearing	housing	kg
ANQ935	UCFL201	12	113	90	15	11	25,5	12	60	33,3	12,7	M10	12160	6318	UC201	FL204	0,45
ANQ936	UCFL202	15	113	90	15	11	25,5	12	60	33,3	12,7	M10	12160	6318	UC202	FL204	0,44
ANQ937	UCFL203	17	113	90	15	11	25,5	12	60	33,3	12,7	M10	12160	6318	UC203	FL204	0,43
ANQ938	UCFL204	20	113	90	15	11	25,5	12	60	33,3	12,7	M10	12160	6318	UC204	FL204	0,41
ANQ939	UCFL205	25	130	99	16	13	27	16	68	35,8	14,3	M14	13300	7457	UC205	FL205	0,58
ANQ940	UCFL206	30	148	117	18	13	31	16	80	40,2	15,9	M14	18525	10735	UC206	FL206	0,86
ANQ941	UCFL207	35	161	130	19	14	34	16	90	44,4	17,5	M14	24415	14630	UC207	FL207	1,08
ANQ942	UCFL208	40	175	144	21	14	36	16	100	51,2	19	M14	27645	16910	UC208	FL208	1,44
ANQ943	UCFL209	45	188	148	22	15	38	19	108	52,2	19	M16	32395	20235	UC209	FL209	1,74
ANQ944	UCFL210	50	197	157	22	15	40	19	115	54,6	19	M16	33345	22135	UC210	FL210	2,1
ANQ945	UCFL211	55	224	184	25	18	43	19	130	58,4	22,2	M16	41230	27930	UC211	FL211	2,91
ANQ946	UCFL212	60	250	202	29	18	48	23	140	68,7	25,4	M20	49780	34390	UC212	FL212	3,74
ANQ947	UCFL213	65	258	210	30	22	50	23	155	69,7	25,4	M20	54340	38095	UC213	FL213	4,57
ANQ948	UCFL214	70	265	216	31	22	54	23	160	75,4	30,2	M20	59090	41895	UC214	FL214	5,11
ANQ949	UCFL215	75	275	225	34	22	56	23	165	78,5	33,3	M20	64030	45885	UC215	FL215	5,37
ANQ950	UCFL216	80	290	233	34	22	58	25	180	83,3	33,3	M22	69065	50350	UC216	FL216	7,2
ANQ951	UCFL217	85	305	248	36	24	63	25	190	87,6	34,1	M22	79800	58805	UC217	FL217	8,61
ANQ952	UCFL218	90	320	265	40	24	68	25	205	96,3	39,7	M22	91295	67925	UC218	FL218	10,51