



SAP	type	dimensions													weight	
		∅d1	H	J	A2	A1	A	2-∅N	L	A0	bolt size	dyn.C	stat.CO	bearing+sleeve	housing	kg
ANR029	UKFL205	20	130	99	16	13	27	16	68	35,5	M14	13300	7457	UK205+H2305	FL205	0,63
ANR030	UKFL206	25	148	117	18	13	31	16	80	39	M14	18525	10735	UK206+H2306	FL206	0,9
ANR031	UKFL207	30	161	130	19	14	34	16	90	42,5	M14	24415	14630	UK207+H2307	FL207	1,17
ANR032	UKFL208	35	175	144	21	14	36	16	100	46,5	M14	27645	16910	UK208+H2308	FL208	1,54
ANR033	UKFL209	40	188	148	22	15	38	19	108	48,5	M16	32395	20235	UK209+H2309	FL209	1,89
ANR034	UKFL210	45	197	157	22	15	40	19	115	50	M16	33345	22135	UK210+H2310	FL210	2,27
ANR035	UKFL211	50	224	184	25	18	43	19	130	54,5	M16	41230	27930	UK211+H2311	FL211	3,06
ANR036	UKFL212	55	250	202	29	18	48	23	140	61	M20	49780	34390	UK212+H2312	FL212	3,79
ANR037	UKFL213	60	258	210	30	22	50	23	155	64	M20	54340	38095	UK213+H2313	FL213	4,48
ANR173	UKFL215	65	275	225	34	22	56	23	165	71	M20	64030	45885	UK215+H2315	FL215	5,48
*	UKFL216	70	290	233	34	22	58	25	180	73,5	M22	69065	50350	UK216+H2316	FL216	7,46
*	UKFL217	75	305	248	36	24	63	25	190	77	M22	79800	58805	UK217+H2317	FL217	9,03
ANR174	UKFL218	80	320	265	40	24	68	25	205	81,5	M22	91295	67925	UK218+H2318	FL218	10,89

* = huomio: kartioholkki myydään aina erkiseen

* = note: adapter sleeve is always sold separately