

Module cases | Modulkåpor | **Moduulikotelot**



MODUULIKOTELOT

Module cases | Modulkåpor | **Moduulikotelot**

Moduulikotelot



Onnline module cases

Stylish Onnline cases have been equipped with shaded doors. The IP65 case material is ASA (Acrylonitrile Styrene Acrylate) and the IP40 case material is ABS (Acrylonitrile Butadiene Styrene) and as well as UV stable structure.

Constructed according to the following standards IEC 60670-1:2002, IEC 60670-24:2005.

Temperature range -25 °C...+60 °C.

Onnline modulkåpor

De snygga Onnline modulkåporna är försedda med mörktonade dörrar. Materialet i IP65 kåporna är ASA (Acrylonitrile Styrene Acrylate) och materialet i IP40 kåporna är (Acrylonitrile Butadiene Styrene) samt UV-stabil sammansättning.

Tillverkas enligt följande standarder: IEC 60670-1:2002, IEC 60670-24:2005.

Temperaturområde -25 C...+60 C.

Onnline-moduulikotelot

Tyylikkää Onnline-moduulikotelot on varustettu tummennetuilla ovilla. IP65-koteloiden materiaalina on ASA (Acrylonitrile Styrene Acrylate) ja IP40-koteloiden materiaalina on ABS (Acrylonitrile Butadiene Styrene) sekä UV stabiilirakenne.

Moduulikotelot on valmistettu IEC 60670-1:2002, IEC 60670-24:2005 -standardien mukaan.

Lämpötila (Temperature range) alue -25 °C...+60 °C.

Fire test for the material in 650 °C (glow wire test) and for PE and N bus bars in 960 °C (glow wire test). (Resistance of insulating material to fire).

Rated voltage range for the cases AC 400V.

We offer three separate product families

- Module cases surface IP65
- Module cases surface IP40
- Module cases built-in IP40

Brandtest på material 650 grader C (glow wire test) samt PE- och N-skenor 960 grader (glow wire test). (Resistance of insulating material to fire).

Spänning i kåporna AC 400V.

Produktfamiljen består av tre olika

- Modulkåpor yta IP65
- Modulkåpor yta IP40
- Modulkåpor infällda IP40

Palotesti materiaalille 650 °C (glow wire test) ja PE- ja N -kiskoille 960 °C (glow wire test). (Resistance of insulating material to fire).

Jännitealue (Rated voltage) koteloidilla AC 400V.

Tuoteperheemme

- Moduulikotelot pinta IP65
- Moduulikotelot pinta IP40
- Moduulikotelot upotettavat IP40

Module cases | Modulkåpor | Moduulikotelot

Moduulikotelot pinta IP65 | Modulkåpor yta IP65 | Module cases surface IP65

Koodi Kod Code	SAP	Tyyppi Typ Type	Mod	PE ja N liitin kontakt connector	pituus x korkeus x leveys längd x höjd x bredd length x height x width
34 690 00	AJJ995	ONNFIN4DIP65	4	2 x 4	127 x 200 x 120
34 690 01	AJJ996	ONNFIN8DIP65	8	2 x 8	200 x 200 x 120
34 690 02	AJJ997	ONNFIN12DIP65	12	2 x 10	318 x 258 x 142
34 690 03	AJJ998	ONNFIN24DIP65	24	2 x 13	318 x 383 x 142
34 690 04	AJJ999	ONNFIN36DIP65	36	2 x 15	318 x 507 x 142



Moduulikotelo pinta IP40 | Modulkåpor yta IP40 | Module cases surface IP40

Koodi Kod Code	SAP	Tyyppi Typ Type	Mod	PE ja N liitin kontakt connector	pituus x korkeus x leveys längd x höjd x bredd length x height x width
34 690 05	AJK000	ONNFIN4-8CIP40	4 - 8	2 x 8	215 x 236 x 112
34 690 06	AJK001	ONNFIN12CIP40	12	2 x 10	287 x 236 x 112
34 690 07	AJK002	ONNFIN18CIP40	18	2 x 13	396 x 236 x 112
34 690 08	AJK003	ONNFIN24CIP40	24	2 x 13	287 x 361 x 112
34 690 09	AJK004	ONNFIN36CIP40	36	2 x 15	287 x 482 x 112



Module cases | Modulkåpor | **Moduulikotelot**

Moduulikotelo upotettava IP40 | Modulkåpor infällda IP40 | Module cases built-in IP40

Koodi Kod Code	SAP	Tyyppi Typ Type	Mod	PE ja N liitin kontakt connector	pituus x korkeus x leveys längd x höjd x bredd length x height x width
34 690 10	AJK005	ONNFIU4-8CIP40	4 - 8	2 x 8	211 x 232 x 70
34 690 11	AJK006	ONNFIU12CIP40	12	2 x 10	283 x 232 x 70
34 690 12	AJK007	ONNFIU18CIP40	18	2 x 13	396 x 232 x 70
34 690 13	AJK008	ONNFIU24CIP40	24	2 x 13	283 x 357 x 70
34 690 14	AJK009	ONNFIU36CIP40	36	2 x 15	283 x 482 x 70

